

Single Channel Fixed Pipette



5/10/20/100/200/1000µl

Introduction:

Manual fixed pipette is a measuring tool that moves the liquid from the original container to another container within a certain range. The unit is microliter (µl). It is characterized by precision and convenience, and is widely used in biological, chemical and other fields. Often used in the laboratory for the removal of a small amount or trace liquid, different specifications, different specifications of the pipette gun supporting the use of different sizes of the gun head.

Features:

- * In line with ergonomic design, comfortable and convenient operation.
- * High precision, precise liquid separation, according to EN/SO8655 standard calibration.
- * Digital window, easy to set the range, at a glance.
- * The low part can be autoclaved without compromising performance and comfort.
- * Calibration tools and silicone grease are included for easy servicing and calibration.
- * The internal air tightness of the product is good, stable and accurate without leakage.
- * Special suction connector design, easy to observe the sealing condition.

Technical Parameters:

Cat No.	Volume	Measured volume µl	Maximum Permissible Systematic Error		Maximum Permissible Random Error	
			±%	±µl	±%	±µl
10102001	5µl	5	0.4	0.02	0.4	0.02
10102002	10µl	10	0.5	0.05	1.1	0.11
10102003	20µl	20	0.5	0.1	0.4	0.08
10102004	100µl	100	0.3	0.3	0.9	0.9
10102005	200µl	200	0.3	0.6	0.1	0.2
10102006	1000µl	1000	0.3	3	0.1	1

Single Channel Fixed Pipette



Features:

- * An ergonomic design, convenience of use and simplicity of operation.
- * Ease of calibration and maintenance.
- * Availability for autoclave of part of the device.
- * Detailed instructions in Chinese and English.
- * A hook, disassembly tool and consumable replacement parts.
- * An ergonomic handle hook design for easy grip in the palm.
- * A clever design for the tip eject button.
- * A clear reading window.
- * Availability for autoclave of the tip and the pusher, also detachable to facilitate cleaning and maintenance.
- * A tip cone made of durable chemical materials, with excellent chemical corrosion resistance.

Technical Parameters:

Cat.No.	Model	Volume Range	Package	Gross Weight(kg)	Package Size(mm)
20002000	BK-FP0.5	0.5µl	50pcs/carton	9.5	490*400*290
20002005	BK-FP1	1µl	50pcs/carton	9.5	490*400*290
20002010	BK-FP5	5µl	50pcs/carton	9.5	490*400*290
20002020	BK-FP10	10µl	50pcs/carton	9.5	490*400*290
20002030	BK-FP20	20µl	50pcs/carton	9.5	490*400*290
20002040	BK-FP25	25µl	50pcs/carton	9.75	490*400*290
20002050	BK-FP50	50µl	50pcs/carton	9.75	490*400*290
20002060	BK-FP100	100µl	50pcs/carton	9.75	490*400*290
20002070	BK-FP200	200µl	50pcs/carton	9.75	490*400*290
20002080	BK-FP250	250µl	50pcs/carton	10.2	490*400*290
20002090	BK-FP500	500µl	50pcs/carton	10.2	490*400*290
20002100	BK-FP1K	1000µl	50pcs/carton	10.2	490*400*290
20002110	BK-FP2K	2000µl	50pcs/carton	10.3	490*400*290
20002120	BK-FP2.5K	2500µl	50pcs/carton	10.3	490*400*290
20002130	BK-FP5K	5000µl	50pcs/carton	10.3	490*400*290
20002140	BK-FP10K	10ml	50pcs/carton	10.3	490*400*290