

-40°C Freezer(Combined Refrigerator And Freezer)



368L

318L/450L

Technical Parameters

Model	BRF-40V368	BRF-40V318	BRF-40V450
Capacity	Upper:183L; Down:185L	318L (Refrigerator 208L, Freezer 110L)	450L (Refrigerator 295L, Freezer 155L)
Type	Vertical		
Temp. Range	Refrigerator: 2°C~8°C Freezer: -10°C~-40°C		
Temp. Accuracy	0.1°C		
Control System	Microprocessor Control		
Alarm	BRF-40V368: High or low temperature alarm, sensor failure alarm, power failure alarm, door open alarm. BRF-40V318/BRF-40V450: Power failure alarm, door ajar alarm, high or low temperature alarm, thermostat failure alarm		
Refrigeration Type	Direct Refrigeration		
Refrigerant	R290		
Compressor	2 compressors		
Material	Structure	Unibody design	
	Internal	304 stainless steel	
	External	Sprayed steel plate	
Door	2pcs		
Consumption	748VA/627W	638VA/460W	638VA/570W
Power Supply	AC220V±10%, 50HZ ; AC110V±10%, 60HZ		
Caster	Yes		
Shelf	Refrigerator: 3pcs Freezer: 1pc		
External Size(W*D*H)	750*736*1884mm	741*631*1889mm	741*811*1889mm
Internal Size(W*D*H)	Upper:580*563*563mm	Refrigerator:590*495*746	
	Down:580*567*563mm	Freezer:520*467*460	
Package Size	890*880*2100mm	880*770*2090	880*950*2090
Gross Weight	195kg	178kg	200kg

Remark: Standard USB, can store 8000 pieces of data per month, data rolling coverage after the limit, can save 120 months of data.

-40°C Freezer



BDF-40V58

BDF-40V90

BDF-40V268

Technical Parameters

Model	BDF-40V58	BDF-40V90	BDF-40V268
Capacity	58L	90L	268L
Type	Vertical		
Temp. Range	-15°C~-40°C		
Temp. Accuracy	0.1°C		
Control System	Microprocessor Control	Microprocessor Control; Digital Display	
Alarm	High or low temperature alarm, sensor failure alarm.	High or low temperature alarm, sensor failure alarm, power failure alarm, door open alarm.	High or low temperature alarm, door ajar alarm, power failure alarm, sensor failure alarm.
Refrigeration Type	Direct Refrigeration		
Refrigerant	R404a and R23	R290	
Compressor	1 compressor	Unicompressor, imported famous brand compressor	International well-known brand
Construction	Structure	Unibody design	
	Internal Material	304 stainless steel	
	External Material	Sprayed steel plate	
Door	1pc	3pcs	4pcs
Consumption	340W/390VA	528VA/252W	484VA/286W
Power Supply	AC220V±10%, 50HZ; AC110V±10%, 60HZ	AC220V±10%, 50/60HZ	AC220V±10%, 50Hz; 110V±10%, 60Hz (Optional)
Caster	Yes		
Shelf	1 pc shelf	2 pcs shelves	3pcs shelves, Stainless Steel
Standard Accessory	/	USB port	
Optional Accessory	USB port	Printer	
External Size(W*D*H)	540*620*1115mm	600*610*945mm	690*744*1631mm
Internal Size(W*D*H)	361*405*406mm	440*447*640mm	520*567*1013mm
Package Size	610*690*1275mm	730*730*1140mm	810*860*1820mm
Gross Weight	98kg	82kg	140kg