

## Bath / Circulator Thermostatic Water Bath



### Features:

- \* PID temperature control, high temperature precision, with temperature deviation alarm.
- \* The water tank is made of 304 stainless steel by one time stamping process, which is resistant to high temperature, corrosion and rust.
- \* All-round heating, rapid heating, adjustable lid locking temperature.
- \* Equipped with a water level sensor, when the water level is lower than the sensor, it will automatically stop heating.
- \* The lid of the water bath can be adapted to various sizes of containers (inside diameter: φ39mm, φ57mm, φ77mm, 97mm).

### Technical Parameters:

Model	BK-S2	BK-S4	BK-S6	BK-S8
Positions	2	4	6	8
Capacity	5L	10L	20L	26L
Temp. Range	RT~100°C			
Temp. Fluctuation	±0.5°C			
Timing Range	0~99h59min			
Display	OLED Display			
Function	Timing function, over-temperature alarm, anti-dry protection			
Consumption	600W	1000W	1500W	2000W
Power Supply	220V±10%, 50/60Hz(Standard);110V, 60Hz(Optional)			
Internal Size(L*W*H) mm	300*150*150	325*300*145	505*300*150	620*315*135
External Size(L*W*H) mm	383*236*259	383*381*264	568*376*259	650*365*264
Package Size (L*W*H) mm	444*324*294	444*324*444	444*324*634	710*400*285
Net Weight	4.24kg	5.72kg	8.02kg	10kg
Gross Weight	4.7kg	6.2kg	8.5kg	13kg

### Optional Tube Rack:

Model		BK-S2	BK-S4	BK-S6	BK-S8
Max Number	φ13mm*40	1	3	5	7
	φ16mm*40	1	3	5	7



### Features:

- \* The shell adopts cold plate spraying, which improves the anti-corrosion ability of the whole machine.
- \* The inner liner is made of high-quality 304 stainless steel, which is corrosion-resistant and not easy to rust.
- \* Adjustable ring cover to meet the needs of different sizes of experimental instruments.
- \* Real-time temperature value display, accurate temperature control, countdown display.
- \* Hidden stretch drain, beautiful, convenient and durable.

### Technical Parameters:

Model	BK-WB1	BK-WB2	BK-WB4	BK-WB6	BK-WB8
Capacity	3.5L	6.8L	13L	20L	26L
Temperature Range	RT+5~99.9°C				
Temperature Display Precision	0.1°C				
Temperature Fluctuation	±0.5°C				
Temperature Uniformity	±0.5°C				
Timing Range	1-999min				
Chamber Material	Integrated S.S.				
Heating Power	500W	600W	800W	1200W	1800W
Power Supply	Standard: 220V 50/60Hz; optional: 110V 50/60Hz				
Chamber Size(mm)	160*160*140	305*160*140	305*305*140	470*305*140	620*305*140
Outer Size(mm)	245*245*195	365*245*195	365*365*195	530*365*195	680*365*195
Net Weight	2.7kg	3kg	4.3kg	5.4kg	7kg
Packing Size(mm)	210*215*195	395*215*240	395*395*240	560*395*240	705*410*265
Gross Weight	3.5kg	3.7kg	5.3kg	6.7kg	8.6kg

### Optional Tube Rack:

Model		BK-WB1	BK-WB2	BK-WB4	BK-WB6	BK-WB8
Max Number	φ13mm*40	/	1	3	5	6
	φ14mm*40	/	1	3	5	5
	φ16mm*40	/	1	3	4	5
	φ17mm*40	/	1	2	4	5
	φ19mm*40	/	1	2	4	5
	φ21mm*40	/	1	2	3	5
	φ23mm*40	/	1	2	3	4
	φ25mm*40	/	/	/	2	2
	φ27mm*40	/	/	/	2	2
	φ30mm*40	/	/	/	1	1
	φ17mm*12	2	4	8	12	15
	φ19mm*12	1	3	5	10	12
	φ21mm*12	/	2	4	8	10
	φ23mm*12	/	2	4	8	10
	φ27mm*12	/	2	3	6	6
	φ30mm*12	/	1	3	5	6
φ32mm*12	/	1	3	5	5	