

Thermostatic Water Tank



BK-W2

BK-W6

BK-W4

Features:

- * All-round heating, rapid temperature rise, adjustable lid locking temperature, constant temperature operation, making the experiment accurate.
- * OLED display, temperature, time and other parameters displayed in real time.
- * Intelligent algorithm monitoring, water shortage stops heating when turned on, and the working time of the instrument can be freely set.
- * The water tank is stamped and formed from stainless steel, which is resistant to high temperatures, corrosion, and rust; it is equipped with a load-bearing frame.

Technical Parameters:

Model	BK-W2	BK-W4	BK-W6
Type	1 row, 2 holes	2 rows, 4 holes	2 rows, 6 holes
Heating Power	600W	1000W	1500W
Chamber	Stainless steel		
Temp. Range	RT~100°C		
Temp. Fluctuation	±0.5°C		
Display	OLED		
Timing	Yes		
Capacity	5L	10L	20L
Power Supply	Standard: AC220V 50/60Hz, optional: AC110V 50/60Hz		
Chamber Size	300*150*150mm	325*300*145mm	505*300*150mm
External Size	385*280*275mm	385*420*275mm	570*420*275mm
Net Weight	6.15kg	7.85kg	11.3kg
Packing Size	444*294*324mm	444*444*324mm	634*444*324mm
Gross Weight	7.8kg	10.5kg	13.6kg

Optional Tube Rack:

Model	BK-W2	BK-W4	BK-W6	
Max	φ13mm*40	1	3	5
Number	φ16mm*40	1	3	5



Constant Temperature Water Tank

Features:

- * Precise Timing
Timer can accurately control the heating time
Timing range: 0~9999 minutes/hours
Timing error: <1%
- * LCD Display
Real-time temperature display countdown display
- * Inside Design
Powder-coated steel outer shell, durable
The fully rounded inner cavity is easy to clean and disinfect
- * Temperature Difference Calibration
Equipped with temperature deviation calibration function
- * Temperature Control
PID microprocessor control
Standard over-temperature alarm function



WT-26

WT-100

Technical Parameters:

Model	WT-26	WT-100
Temp. Range	R.T.+5~100°C(Normal atmosphere)	
Temp. Fluctuation	±0.5°C	≤±2°C
Temp. Accuracy	0.1°C	
Capacity	30L	100L
Consumption	1500W	
Power Supply	220VAC±10%, 110VAC±10%; 50/60Hz	
Lid Size	Φ37, Φ58, Φ79, Φ100, Φ120	
Internal Size(L*W*D)	500*300*200mm	1330*450*170mm
External Size(L*W*D)	665*364*281mm	1501*523*288mm
Package Size(L*W*D)	710*405*330mm	1550*575*330mm
Net Weight	15kg	40kg
Gross Weight	18kg	45kg

Features:

- * Microprocessor control, LED display.
- * Timing function and over-temperature protection.
- * External material: Cold rolled steel with anti bacteria powder coating.
- * Inner material: Stainless steel inner chamber.



WT-42

WT-60

Technical Parameters:

Model	WT-42	WT-60
Capacity	13.6L	32L
Temp. Range	RT+5-100°C	
Temp. Fluctuation	≤±0.5°C	
Consumption	800W	1500W
Power Supply	AC110V/220V±10%, 50/60Hz	
Internal Size(L*W*H) mm	420*180*180	600*300*180
External Size(L*W*H) mm	580*250*270	760*370*270
Package Size(L*W*H) mm	640*310*310	820*440*310
Net Weight	10kg	15kg
Gross Weight	11kg	17kg