

Climate Incubator



BJPX-A250/II BJPX-A300/II  
BJPX-A400/II

BJPX-A300III

Features:

- \* Microprocessor PID control, accurate and stable.
- \* Magnetic door sealing.
- \* LED Display for BJPX-A series, LCD display for BJPX-All and AllI series.
- \* CFC-free refrigerant, eco-friendly and highly efficient.

Safety Functions:

- \* Over temperature protection.
- \* Temperature sensor for open circuit or short circuit protection.
- \* Parameters can be saved automatically when power off or system error.

Optional Accessories:

Printer (only for BJPX-All series).

Notice:

Please don't keep setting the temperature lower than 20°C for more than 160h.

Technical Parameters:

Model	BJPX-A250/II	BJPX-A300/II	BJPX-A300III	BJPX-A400/II
Capacity	248L	290L	300L	403L
Lighting Type	BJPX-A series: 2-side illumination; BJPX-All and AllI series: 3-side illumination			
Temp. Range	With illumination: 10~50°C, Without illumination: 5~50°C			
Temp. Fluctuation	±0.5°C		±1°C	±0.5°C
Temp. Uniformity	±2°C			
Humidity Range	With illumination: 50%~80% (18~45°C); Without illumination: 50%~90% (15~45°C)			
Lighting Illumination	BJPX-A250/300/400: 0~6000 Lux (6-grade adjustable) BJPX-A250II/300II/400II: 0~12000 Lux (5-grade adjustable) BJPX-A300III: 0~20000 (6-grade adjustable)			
Ambient Temp.	5~35°C			
Continuous Working Time	≥180h			
Shelves	3 pcs/adjustable			
Consumption	2400W	2900W	1500W	3400W
Power Supply	BJPX-A and All series: AC220V, 50/60Hz(Standard); BJPX-AllI series: AC220V, 50Hz(Standard); AC220V,60Hz; AC110V,60Hz;(Optional)			
Internal Size(W*D*H) mm	470*449*1178	490*464*1278	520*550*1140	560*600*1198
External Size(W*D*H) mm	672*892*1825	691*907*1925	830*850*1850	764*1032*1860
Package Size(W*D*H) mm	800*1010*1990	790*1040*2090	950*930*2100	890*1150*2030
Gross Weight(kg)	148	158	300	200