

## Thermostatic Water Bath



### Introduction:

It is a three-well thermostatic water bath with independent temperature control. The independent three-well thermostatic water bath is used in medical and health care, medical colleges, industrial and scientific research institutions for precision constant temperature, auxiliary heating, gene amplification and other experiments.

### Feature:

- \* Three-well independent temperature control, high efficiency.
- \* Rapid heating, precise temperature control.
- \* Automatic alarm: Sensor fault alarm, over temperature alarm, upper and lower temperature deviation alarm.
- \* The shell is made of high-quality sheet and plastic spray, the inner liner material and top cover are made of stainless steel, with the characteristics of high temperature resistance and corrosion resistance.

### Technical Parameters:

Model	BK-DS3
Capacity	2.5L*3
Temp. Range	RT+5°C~100°C
Temp. Precision	0.1°C
Temp. Fluctuation	±1°C
Temp. Uniformity	±0.5°C(AT37°C)
Top Cover Inner Liner Material	Stainless steel
Timing Range	0~999min
Opening Size	(150*136mm)*3
Consumption	300W*3
Power Supply	AC220V, 50/60Hz; 110V, 50/60Hz
Internal Size(L*W*H)	(150*140*120mm)*3
External Size(L*W*H)	660*220*250mm
Net Weight	7.62kg
Packing Size(L*W*H)	700*320*295mm
Gross Weight	9kg

## Thermostatic Water Bath



### Features:

- \* Three-well independent temperature control, high efficiency.
- \* Rapid heating, precise temperature control.
- \* Automatic alarm: Sensor fault alarm, over temperature alarm, upper and lower temperature deviation alarm.
- \* Temperature deviation calibration function.
- \* The shell is made of cold-rolled steel and is treated with environmentally friendly spraying, which ensures excellent corrosion resistance and prevents rusting easily.

### Technical Parameters:

Model	WB-8D
Capacity	3.9L*3
Temp. Control	PID digital temperature control
Temp. Range	RT~100°C(Normal atmosphere)
Temp. Fluctuation	±0.5°C
Temp. Precision	±0.5°C
Temp. Resolution	0.1°C
Temperature Uniformity	±0.5°C
Timing Range	0~9999 or continuous
Heating Mode	Stainless steel tubular heating
Consumption	900W
Power Supply	Standard: AC220V, 50Hz; optional: AC110V; 50Hz
Internal Size(L*W*H)	(150*174*148)*3mm
External Size(L*W*H)	533*311*260mm
Net Weight	10kg
Package Size(L*W*H)	573*300*345mm
Gross Weight	13kg