

Magnetic Stirring Water Bath



Features:

- * High-quality cold-rolled steel plate outer shell, the surface is sprayed with environmental protection spray processing, good corrosion resistance.
- * Good performance, no noise, no vibration, fast heating
- * Artistic and reasonable, easy to maintain
- * LED display, real-time temperature display

Technical Parameters:

Model	MSW-101S
Display	LED
Heating Temp. Range	RT+5~100°C
Temperature Precision	±1°C
Stirring Speed	0~2600rpm
Stirring Capacity	50~2000ml
Stirring Power	2.5W
Heating Consumption	600W
Power Supply	Standard: AC220V, 50/60Hz; optional: AC110V, 50/60Hz
Work Plate Size	Φ200*100mm
External Size(W*D*H)	340*340*290mm
Net Weight	6.4kg
Package Size(W*D*H)	390*390*360mm
Gross Weight	10kg

Note:

1. Please use a three-phase safety socket and properly grounded.
2. The instrument should be kept clean, it should be cut off the power supply when long-term not using.
3. Do not open the temperature control switch when the stainless steel container is not added with thermal oil and the temperature sensor is not connected, so as to avoid damage to the heating element and constant temperature meter.

Thermostatic Shaking Water Bath



Application:

Suitable for BOD measurement in water analysis, cultivation and preservation of bacteria, viruses, molds, and microorganisms, plant cultivation, breeding experiments, and other applications.

Features:

- * Shaking speed: 40~300 rpm.
- * Temperature control range: RT+5°C to 100°C, with rapid heating.
- * LED display, independent control of temperature and speed.
- * Selectable timed or continuous operation mode.
- * Inner chamber made of 304 stainless steel, rust-resistant and easy to clean.
- * Comes standard with a universal spring clamp.

Technical Parameters:

Model	BK-WBS30C	BK-WBS30R
Shaking Amplitude	20mm	
Shaking Method	Rotatory shaking	Reciprocating shaking
Display	LED Display	
Speed Range	40~300rpm	
Temp. Range	RT+5°C~100°C	
Temp. Precision	±0.5°C	
Timing Range	1~9999min/Continuous	
Standard Tray Configuration	1 pc, universal spring clip	
Tray Size	410*310mm	
Max Load	20kg	
Consumption	1500W	
Power Supply	Standard: AC220V, 50/60Hz; optional: AC110V, 50/60Hz	
External Size(L*D*H)	715*550*490mm	
Net Weight	34kg	
Package Size(L*D*H)	770*625*580mm	
Gross Weight	40kg	