

Thermostatic Oil Bath



Introduction:

Thermostatic oil bath is a kind of laboratory equipment that realizes accurate temperature control and uniform heating by heating oil. It is used in biology, physics, chemical, medical, environmental protection and other experimental science fields or auxiliary heating precision products.

Feature:

- * High efficiency heating, maximum temperature up to 300°C.
- * Microcomputer control, more accurate temperature control, more accurate temperature regulation.
- * The stainless steel inner liner has the advantages of strong corrosion resistance.

| Technical Parameter | s: hinhase | | hinhase | |
|----------------------|------------------------------|---------------|---------------|---------------|
| Model | BK-OB5 | BK-OB10 | BK-OB15 | BK-OB20 |
| Capacity | 5L | 10L | 15L | 20L |
| Temp. Range | RT+5°C~300°C | | | |
| Temp. Fluctuation | ±0.5℃ | | | |
| Temp. Precision | ±1℃ | | | |
| Display | LED Display | | | |
| Consumption | 1000W | 1500W | 1800W | 1800W |
| Power Supply | AC220V,50/60Hz; 110V,50/60Hz | | | |
| Internal Size(L*W*H) | 180*180*150mm | 260*260*150mm | 310*310*150mm | 280*280*300mm |
| External Size(L*W*H) | 380*270*220mm | 460*350*220mm | 510*400*220mm | 440*340*340mm |
| Net Weight | 4.5kg | 7.5kg | 9.5kg | 10kg |
| Packing Size(L*W*H) | 405*295*245mm | 485*375*245mm | 535*425*245mm | 530*420*430mm |
| Gross Weight | 5.5kg | 8.5kg | 11kg | 12.5kg |

Thermostatic Oil Bath



Features:

- * LED display.
- * Automatic protection for overheating.
- * Material: Main body is made of steel plate with Baking varnish; The inner liner is made of imported stainless steel.
- * Advanced recycle pump system ensures good evenness of temperature(OB-2).

Technical Parameters:

| Model E-mail e | X OB-1 Tobiok | OB-2 | | |
|---------------------------|------------------------|---------------|--|--|
| Capacity | 23.5L | 37L | | |
| Temperature Range | RT~300℃ | 100030.00111 | | |
| Temperature Fluctuation | ≤1°C | | | |
| Temperature Precision | ≤1°C | | | |
| Display | LED Display | LED Display | | |
| Consumption | 2000W | 2000W | | |
| Power Supply | 110V/220V±10%, 50/60Hz | | | |
| Circulatory System | None | Have | | |
| Circuation Pump Flow Rate | None | 6L/min | | |
| Internal Size(L*W*H) | 280*280*300mm | 300*300*280mm | | |
| Package Size(L*W*H) | 520*420*400mm | 710*460*570mm | | |
| Gross Weight | 15kg | 33kg | | |