

Thermostatic Oil Bath



Features:

- \* LED display
- \* Automatic protection for overheating
- \* Material:Main body is issteel plate with baking varnish; Internal is imported stainless steel
- \* Advanced recycle pump system ensures good evenness of temperature(OB-2)

Technical Parameters:

Model	OB-1	OB-2
Temperature Range	RT~300℃	
Temperature Fluctuation	≤1℃	
Temperature Control Precision	≤1℃	
Heating Power	2000W	
Power Supply	110V/220V±10%,50/60HZ	
Circulatory System	None	Have
Circuation Pump Flow Rate	None	6L/min
Workroom Cubage	280*280*300mm³	300*300*280mm³
Package Size(W*D*H)	520*420*400mm	710*460*570mm
Gross Weight	15kg	33kg

Thermostatic Oil Bath



Application:

Widely used in scientific research, colleges and other enterprises and institutions laboratory distillation, drying, oncentration, temperature stain chemical or biological products, can also be used for constant temperature testing experiments and auxiliary heating.

Features:

- \* The inner liner is made of stainless steel plate and precision machining technology
- \* High temperature and corrosion resistance
- \* Short heat balance time and small temperature fluctuation
- \* LED display of test data, intuitive and accurate

Technical Parameters:

Model	BJPX-OB2
Temperature Control Range	RT+5~300℃
Temperature Fluctuation	≤1℃
Power	600W
Capacity	3.54L
Heating Medium	High temperature thermal oil or distilled water
Power Supply	Standard: 220V 50/60Hz, optional: 110V 50/60Hz
External Size	235*265*190mm
Packing Size	330*330*300mm
Gross Weight	4kg