

### -40°C Freezer



BDF-40V362

BDF-40V398

BDF-40V450

#### Technical Parameters

Model	BDF-40V362	BDF-40V398	BDF-40V450
Capacity	362L	408L	450L
Type	Vertical		
Temp. Range	-15°C~-40°C	-10°C~-40°C	-15°C~-40°C
Temp. Accuracy	0.1°C		
Control System	Microprocessor Control; Digital Display		
Alarm	High or low temperature alarm, door ajar alarm, power failure alarm, sensor failure alarm	High or low temperature alarm, sensor failure alarm	High or low temperature alarm, door ajar alarm, power failure alarm, sensor failure alarm
Refrigeration Type	Direct cooling	Direct Refrigeration	Direct cooling
Refrigerant	R290	CFC free	R290
Compressor	Well-known brand	International well-known brand	Well-known brand
Construction	Structure	Uniboday design	
	Internal Material	Stainless steel	
	External Material	Painted steel panel	Painted steel panel, 150mm foaming insulation
Inner Door	5pcs	4pcs	5pcs
Consumption	484VA/278W	420W/470VA	946VA/510W
Power Supply	AC220V±10%, 50Hz; 110V±10%, 60Hz	AC220V±10%, 50/60Hz; 110V±10%, 60Hz	Standard: 220V 50Hz, optional: 220V 60Hz, 110V 60Hz
Caster	Yes		
Shelf	4pcs	3pcs shelves, Stainless Steel	4pcs
Standard Accessory	USB port	/	USB port
Optional Accessory	Printer	USB port	Printer
External Size(W*D*H)	690*744*1885mm	890*900*1780mm	750*905*1885mm
Package Size	840*860*2050mm	980*1000*1950mm	855*1000*2080mm
Gross Weight	155kg	215kg	180kg

### -40°C Freezer



BDF-40V608

BDF-40V708

BDF-40V808

BDF-40V936

#### Technical Parameters

Model	BDF-40V608	BDF-40V708	BDF-40V808	BDF-40V936
Capacity	608L	708L	808L	936L
Type	Vertical			
Temp. Range	-10°C~-40°C			-20°C~-40°C
Temp. Accuracy	0.1°C			
Control System	Microprocessor control, LED Digital Display			
Audible and Visual Alarm	High and low temperature alarm, sensor failure alarm. (BDF-40V608, BDF-40V708, BDF-40V808)			
	High and low temperature alarm, sensor failure alarm, thermostat failure alarm, power failure alarm, door open alarm, ambient temperature alarm, condenser failure alarm, filter inspection alarm, abnormal voltage alarm, low battery alarm. (BDF-40V936)			
Alarm Method	Sound beeps and lights flash			
Refrigeration Type	Direct refrigeration			
Refrigerant	R404A and R23			R404A
Construction	Foam Layer Thickness	120mm		150mm
	Internal Material	304 stainless steel		
External Material	Sprayed steel plate			
Inner Door	4pcs			
Consumption	1000W/1050VA			1000W/950VA
Power Supply	AC110V/220V±10%, 50/60Hz			
Caster	Yes			
Shelf	3pcs			
Optional Accessory	USB port	USB port	USB port	USB port, Printer
External Size(W*D*H) mm	945*1030*1975	1240*1000*2000	1090*1010*2025	1304*1000*2017
Package Size (W*D*H) mm	1120*1080*2010	1280*1080*2150	1280*1080*2150	1360*1135*2170
Gross Weight	288kg	345kg	370kg	416kg