

-40°C Freezer



BDF-40V368D



BDF-40V528D

Technical Parameters

Model	BDF-40V368D	BDF-40V528D
Capacity	368L	528L
Type	Vertical	
Temp. Range	-10°C~-40°C	
Temp. Accuracy	0.1°C	
Control System	Electronic temperature control	
Alarm	Power failure alarm, door ajar alarm, high or low temperature alarm, thermostat failure, battery switch alarm	
Cooling Method	Direct cooling	
Refrigerant	R290	
Condenser	Bundy tube	
Construction	Structure	Unibody design and thickened environmental protection foam insulation layer
	Internal Material	304 stainless steel
	External Material	Pre-coated galvanized plate
Inner Door	4pcs	
Consumption	880VA/861W	902VA/909W
Power Supply	Standard: AC220V±10% 50Hz; optional: AC110V±10% 60Hz	
Caster	Yes	
Shelf	4pcs	
Standard Accessory	USB port	
External Size(mm)	750*736*1884	890*810*1884mm
Internal Size(mm)	Up:580*575*563; Down: 580*575*563	Up:720*649*563; Down: 720*649*563
Package Size(W*D*H) mm	890*880*2100	1030*950*2100
Gross Weight	195kg	220kg

-40°C Freezer



BDF-40H110



BDF-40H210



BDF-40H310



BDF-40H485

Technical Parameters

Model	BDF-40H110	BDF-40H210	BDF-40H310	BDF-40H485
Capacity	110L	210L	308L	485L
Temperature Range	-15°C~-40°C			-20°C~-40°C
Temperature Accuracy	0.1°C			
Control System	Microprocessor Control, LED Display			
Alarm	BDF-40H110&BDF-40H210&BDF-40H310: High or low temperature alarm, Sensor failure, Power failure, Battery switch alarm BDF-40H485: High or low temperature alarm, sensor failure alarm, Power failure alarm, Temperature controller failure alarm			
Refrigeration Type	Direct Refrigeration			
Refrigerant	R290, 55g	R290, 60g	R290, 70g	R290
Evaporator	Material of Copper			
Construction	Structure	Unibody Design & Mono-assembly foaming (Rigid polyurethane insulation material)		
	Internal material	304 Stainless Steel		
	External material	Powder coated cold rolled steel plate		
Consumption	550VA/270W	550VA/280W	528VA/290W	295W/290VA
Power Supply	Standard: 220V 50Hz; optional: 110/220V 60Hz			Standard: 220V 50/60Hz; optional: 110V 50/60Hz
Caster	Yes			
Optional Accessory	USB port			
External Size(L*W*H) mm	705*705*885	945*785*885	1225*790*885	1655*755*915
Package Size(L*W*H) mm	805*800*1015	1045*880*1015	1325*885*1015	1775*900*1060
Gross Weight	73kg	88kg	101kg	138kg