# **BIOBASE®**

## **Cryostat Microtome**

### Applications:

It is an essential product for rapid sectioning of pathological tissues, and is mainly suitable for quick frozen sectioning in large, medium and small hospitals, medical colleges, research institutes, animal husbandry, histology, pathology, forensic identification, etc.



#### Features:

- \* This machine adopts a more reasonable structural design suitable for scientific research, clinical, large, medium, small, and hospital pathological frozen sections.
- \* Four key cooling points are designed, all of which can be automatically adjusted according to the temperature required for slicing to ensure the speed and quality of slicing.
- \* The mechanical parts of the slicer are all made of high-quality materials, precision processed and assembled, and the core is a closed structure, free of maintenance.
- \* Knife feeding and retracting are electric control.
- \* There is no need to turn on day and night, no need to pre-cool, and it will enter the frozen state within ten minutes after turning on.
- \* The trimming thickness and slice thickness can be set by yourself.
- \* It has two functions of automatic defrosting and manual defrosting.
- \* Editing and slicing can be freely converted.
- \* It has lighting and ultraviolet disinfection functions, and the freezer is equipped with a water pipe, which is convenient for cleaning.

## **Technical Parameters:**

Model	BK-2328	
Section Thickness Range	1-100µm	
Trimming Thickness Range	10-400µm	
Chamber Temp. Range	-10°C to -40°C	
Specimen Head Temp. Range	-10°C to -40°C	
Time to The Lowest Temperature	60min	
Lowest Temp. of Refrigerating Table	-45℃	
Lowest Temp. of Peltier Together with Refrigerating Table	-60°C	
Max Specimen Size	55*60mm	
Specimen Vertical Stroke	72mm	
Specimen Horizontal Stroke	22mm	
Electric Coarse Feed	Rapid 0.7mm/s, slow 0.35mm/s	
Power Supply	Standard: 220V 50/60Hz, optional: 110V 50/60Hz	
Power	500W	
External Size	770*840*1190mm	
Packing Size	850*940*1400mm	
Gross Weight	165kg	

## **Tissue Embedding Center**

#### Features:

- \* Fully automatic program control, can be preset to start on any day within a week
- \* The temperature control adopts a single-chip microprocessor controller, and the temperature setting is simple
- \* Using a new type of heating element, fast heating, uniform heating, energy saving and reliable
- \* Double overheating protection device, safe and reliable
- \* With memory function, automatically retain the preset temperature after operation
- Novel appearance, split design, embedding machine, freezing table, random combination
- \* Enlarging the left and right boxes, suitable for all kinds of dehydration baskets, the inner and outer boxes are separated, easy to clean and maintain
- \* Equipped with a metal hose magnifying glass, it is suitable for very small sample tissue operations

## Technical Parameters:

Model	BK-TEV
Thermal Temperature Range	RT-80℃
Control Temperature Precision	±3℃
Timing Range	0-24h
Paraffin Chamber Size	650*130*97mm
Thermal Storage Size	240*240*57mm, two pcs
Working Area Size	700*93mm
Power	≤1100W
Power Supply	Standard: 220V 50/60Hz, optional: 110V 50/60Hz
Machine Size	672*735*383mm
Net Weight	41kg
Packing Size	850*880*650mm
Gross Weight	72kg (Add extra 10kg for 110V)

## **Tissue Embedding Center**

## Features:

- \* Environmentally friendly fluorine-free refrigerant is selected, with low noise and fast cooling effect
- \* The temperature control adopts a single-chip microprocessor controller, and the temperature setting is simple
- $\ensuremath{\ast}$  With temperature control mode and super cooling mode, high temperature control accuracy
- st The cooling temperature can be adjusted to achieve the ideal cooling effect

### Technical Parameters:

echilical Farameters.	
Model	BK-CPIV
Temperature Control Range	5 to -20°C(Max to -28°C)
Control Temperature Precision	±1℃
Working Area Size	360*300mm
Power	300W
Power Supply	Standard: 220V 50/60Hz, optional: 110V 50/60Hz
Machine Size	630*350*400mm
Net Weight	23kg
Packing Size	480*770*590mm
Gross Weight	40kg (Add extra 10kg for 110V)

Remark: The above two products should be used together.



265 266