

Tissue Embedding Center



Features:

- * Fully automatic program control, can be preset to start any day within a week.
- * The temperature control adopts a single-chip microprocessor controller, and the temperature setting is simple.
- * Using a new type of heating element, the heating is fast, the heating is uniform, and the energy saving is reliable.
- * Equipped with a small cooling platform, the base mold paraffin can be quickly pre-cooled.

Technical Parameters:

Model	BK-TEI
Thermal Temperature Range	RT~80℃
Control Temperature Precision	±3℃
Timing Range	0~24h
Paraffin Chamber Size	350*145*80mm
Thermal Storage Size	205*145*60mm, two pcs
Working Area Size	500*145mm
Power	1100W
Power Supply	AC220V, 50/60Hz(Standard); AC110V, 60Hz(Optional)
External Size(W*D*H)	525*550*500mm
Net Weight	36kg
Packing Size(W*D*H)	650*660*660mm
Gross Weight	43kg

Tissue Flotation Water Bath &Slide Dryer



Applications:

It is suitable for medical diagnosis, biological research, epidemic prevention, forensic identification.

Features:

- * Integrating spreading, baking and roasting slices in one, compact structure (small space occupation), novel shape and easy operation.
- * The film drying box can dry the film at a constant temperature and can accommodate 3 dyeing racks.
- * The louver-style grilling table top has a large capacity (60 slides are actually arranged), easy to put and take out, and the grilling effect is better.
- * High-brightness LCD display, real-time display of sheet spreading and drying sheet temperature, simple and clear.
- * Highly sensitive temperature control integrated unit, high precision and reliable performance.
- * With over-temperature alarm function.
- * Using new heating software, fast heating, uniform heating, small thermal inertia, reliable energy saving.
- * With memory function, automatically retain the set temperature after operation.
- * The work surface is spray-coated, corrosion-resistant.

Technical Parameters:

Model	BTH-VI
Temperature Range	RT~99℃
Temperature Precision	±1℃
Over Temperature Alarm Range	1~5℃
Water Tank Size	220*150mm*65mm
Drying Plate Size	260*150mm
Oven Size	200*100*110mm
Power	≤680W
Power Supply	AC220V, 50/60Hz(Standard); AC110V, 60Hz(Optional)
External Size(W*D*H)	590*340*225mm
Package Size(W*D*H)	650*410*240mm
Net Weight	9.2kg
Gross Weight	10kg