

Tissue Flotation Water Bath



Features:

- * High-brightness LCD display, real-time display of temperature.
- * Highly sensitive temperature control integrated unit, high precision and reliable performance.
- * With over-temperature alarm function
- * Using new heating materials, heating fast, uniform heating, low thermal inertia, energy saving and reliable.
- * With memory function. The set temperature is automatically retained.
- * The work surface is sprayed for corrosion resistance.

Technical Parameters:

Model	BT-I
Temp. Range	RT~99°C
Temp. Precision	±1°C
Over-temp. Alarm Range	1~5°C
Environmental Temp. Range	0~40°C
Bath tank Size(W*D*H)	240*180*55mm
Display	LCD
Power Supply	AC220V±10%, 50/60Hz(Standard); AC110V±10%, 60Hz(Optional)
Consumption	200W
External Size(W*D*H)	345*340*130mm
Package Size(W*D*H)	410*410*200mm
Net Weight	5kg
Gross Weight	6kg

Slide Dryer (Hot Plate)



BH-I



BH-II

Features:

- * High-brightness LCD display, real-time display of temperature.
- * Highly sensitive temperature control integrated unit, high precision and reliable performance.
- * With over-temperature alarm function
- * Using new heating materials, heating fast, uniform heating, low thermal inertia, energy saving and reliable.
- * With memory function. The set temperature is automatically retained.
- * The work surface is sprayed for corrosion resistance.
- * Louver table, 65°inclination Angle, large capacity. (Only for BH-II)

Technical Parameters:

Model	BH-I	BH-II
Temp. Range	RT~99°C	
Temp. Precision	±1°C	
Environmental Temp. Range	0~40°C	
Over-temp. Alarm Range	1~5°C	
Drying Area	345*260mm	
Number of Slides	40	65
Display	LCD	
Power Supply	AC220V±10%, 50/60Hz(Standard); AC110V±10%, 60Hz(Optional)	
Consumption	200W	
External Size(W*D*H)	345*340*130mm	
Package Size(W*D*H)	410*410*200mm	
Net Weight	5kg	
Gross Weight	6kg	