

# Paraffin Dispenser



#### Features:

- \* The LCD screen displays the heating status.
- \* Adopt new heating element, heating fast, energy saving and reliable.
- \* Paraffin valve intelligent control heating control, to ensure smooth wax.
- \* Imported temperature measuring integrated block, high precision, stable performance.
- st With memory and automatic recovery function, automatically save preset temperature after running.
- \* Full computer automatic control program, intelligent digital temperature controller, real-time temperature display.

#### Technical Parameters:

| Model           | BK-RLY   |  |
|-----------------|--|--|
| Capacity        | 12L  |  |
| Temp. Range     | RT~100℃  |  |
| Temp. Precision | ±1℃  |  |
| Consumption     | 1000W  |  |
| Power Supply    | Standard: 220V 50/60Hz, optional: 110V 50/60Hz |  |
| External Size   | 330*430*550mm                                  |  |
| Net Weight      | 15kg   |  |
| Packing Size    | 440*560*700mm                                  |  |
| Gross Weight    | 27kg   |  |

## **Slides Cabinet**



### Technical Parameters:

| Model                |                | BKC-E1-1  | BKC-E2-1          | BKC-E3           |
|----------------------|----------------|---|-------------------|------------------|
| Capacity             |                | 72 drawers  | 18 drawers        | 18 drawers       |
|                      |                | Loading: 64800pcs   | Loading: 12000pcs | Loading: 9000pcs |
|                      |                | glass slides  | paraffin block    | glass slides     |
| Material             |                | Cold-rolled steel plate   |                   |                  |
|                      | Cabinet        | Surface treatment: degreasing and oil removal, surface conditioning, zinc-based |                   |                  |
|                      |                | phosphating, passivation, powder coating  |                   |                  |
|                      | Drawer         | Cold-rolled steel plate   |                   |                  |
|                      | Slot           | Special slot for metal die opening  |                   |                  |
|                      | Marking Groove | Integral stamping forming   |                   |                  |
| External Size(W*D*H) |                | 403*478*1625mm  | 450*478*1295mm    |                  |
| Package Size(W*D*H)  |                | 470*550*430mm*3   | 505*535*445mm*2   |                  |
|                      |                | 470*550*555mm*1   | 505*535*570mm*1   |                  |
| Net Weight           |                | 21.6kg*3  | 22.2kg*2          | 20.5kg*2         |
|                      |                | 23.52kg*1   | 24.21kg*1         | 22.51kg*1        |
| Gross Weight         |                | 23.26kg*3   | 23.38kg*2         | 22.21kg*2        |
|                      |                | 25.18kg*1   | 24.24kg*1         | 24.22kg*1        |

274