

Mould Incubator



LCD Display



USB Port

Application:

This series of products are widely used in medical and health, epidemic prevention and inspection, biopharmaceuticals, animal husbandry research, environmental protection, agricultural scientific research and other fields.

Features:

- * LCD display.
- * The refrigeration adopts a new fluorine-free design to ensure green and environmental protection.
- * With parameter memory function, the call will automatically resume operation.
- * The inner box is designed with a circular arc structure, which is easy to clean.
- * Pullable movable shelves with adjustable spacing.
- * The inner box is equipped with a fan to form a micro air circulation to improve the temperature uniformity in the box.
- * Outer box material: cold-rolled steel plate sprayed on the surface; internal material: SUS304 stainless steel plate.

Technical Parameters:

| Model | BJPX-M80N | BJPX-M100N | BJPX-M150N | BJPX-M200N | BJPX-M250N | BJPX-M300N | BJPX-M400N |
|---|---|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|
| Capacity | 80 | 100 | 150 | 200 | 250 | 300 | 400 |
| Temp.Control Range | 0°C~65°C(Microcomputer PID control) | | | | | | |
| Humidity Range | 50%~90%RH(Microcomputer PID control) | | | | | | |
| Temp.Uniformity | ±2°C | | | | | | |
| Temp.Fluctuation | ±1°C | | | | | | |
| Humidity Fluctuation | ±5~8%RH | | | | | | |
| Temperature and Humidity Display Accuracy | 0.1°C / 1%RH | | | | | | |
| Timing Range | 0~9999min(h) | | | | | | |
| Power Consumption | 1200W | 1200W | 1200W | 1300W | 1300W | 1500W | 1500W |
| Refrigerant | R134a | | | | | R134a | R404a |
| Power | AC220V, 50/60Hz(Standard); AC110V,60Hz(Optional) | | | | | | |
| Accessories | Standard: Socket, lighting; Optional:USB interface, Printer | | | | | | |
| External Size(W*D*H) | 540*580 *1110mm | 540*580 *1230mm | 590*630 *1390mm | 590*660 *1540mm | 620*700 *1610mm | 660*700 *1710mm | 720*760 *1810mm |
| Internal Size(W*D*H) | 400*370 *560mm | 400*370 *680mm | 450*420 *850mm | 450*450 *1000mm | 480*490 *1070mm | 520*500 *1170mm | 580*540 *1270mm |
| Package Size(W*D*H) | 670*710 *1280mm | 670*710 *1400mm | 720*760 *1560mm | 720*790 *1710mm | 750*830 *1780mm | 790*830 *1880mm | 850*880 *1980mm |
| Net/Gross Weight | 75/90kg | 80/95kg | 100/130kg | 105/148kg | 113/157kg | 125/167kg | 145/180kg |

* Notice:It cannot be used for long-term refrigeration and storage.