

### Commercial Dehumidifier



**Features:**

- \* Microcomputer control, intelligent operation
- \* LED display, indicate humidity
- \* Low temperature available, efficient automatic defrosting system
- \* Timing range: 1~24 hours
- \* Pipe continue drainage function

**Technical Parameters:**

Model	BKDH-890D	BKDH-8138D
Humidity Removal Capacity	90L/24H	138L/24H
Humidity Adjusted Range	10%~90%RH	
Air Circulation	1100 m³/h	1200 m³/h
Refrigerant	R410A	
Material	Cold Rolled Plate Coating	
Applying Area	90~150 m²	130~180 m²
Power Supply	Standard: 220V 50Hz, Optional: 110V 60Hz	
Consumption	1300W	1500W
External Size (W*D*H)	480*420*960mm	480*420*1060mm
Packing Size (W*D*H)	550*470*1060mm	550*470*1150mm
Net Weight	50kg	60kg
Gross Weight	55kg	65kg

### Industrial Dehumidifier



**Features:**

- \* With memory function in case of power-failure
- \* World famous brand compressor, and high-quality centrifugal fan with low noise
- \* Microcomputer automatic control, large LED display
- \* 10L built-in water tank or external pipe is available (for BKDH-6.8DT)
- \* Equipped with a handle and big wheels, mobile and portable (for BKDH-6.8DT)
- \* Timing range: 1~24 hours
- \* Automatic defrost system with high-efficiency
- \* Automatic fault diagnosis function
- \* Continuous pipe drainage function

**Technical Parameters:**

Model	BKDH-6.8DT	BKDH-12KT	BKDH-15KT	BKDH-20KT
Humidity Removal Capacity	7L/h	10L/h	16L/h	20L/h
Working Condition	At 30°C, 80% humidity, it achieves maximum dehumidifying capacity			
Air Circulation	2000m³/h	2800m³/h	4000m³/h	5600m³/h
Refrigerant	R410A			
Control Precision	±5%RH			
Applying Area	180~230 m²	250~350 m²	350~400 m²	450~550 m²
Applicable Temperature	5~38°C			
Defrost	Auto Defrost			
Consumption	2100W	3800W	6100W	8000W
Drainage Type	10L Water tank(standard) or external pipe		External pipe	
Power Supply	Standard: 220V 50Hz, Optional: 220V 60Hz		Standard: 380V, 50Hz Optional: 380V 60Hz, 480V 50/60Hz	
External Size(W*D*H)	525*740*1155mm	770*470*1630mm	1095*485*1750mm	1095*485*1750mm
Package Size(W*D*H)	770*590*1260mm	870*570*1640mm	1105*495*1760mm	1280*620*1900mm
Net Weight	95kg	140kg	250kg	270kg
Gross Weight	100kg	150kg	260kg	280kg