

TopPette-Mechanical Fixed Volume Pipettes



- Features:**
- * Light weight, ergonomic, low force design.
 - * Digital display clearly reads volume setting.
 - * The pipettes cover volume range of 5μl to 5ml.
 - * Easy to calibrate and maintain.
 - * The lower part is autoclavable.
 - * Design helps avoid repetitive strain injuries.

Technical Parameters:

Qpette Series Cat.No.	Volume Range	Test Volume(μl)	Maximume Permissible Systematic error (Inaccuracy)		Maximum Permissible Random error (Inaccuracy)	
7010102018	5μl	5μl	1.3%	0.065μl	1.2%	0.06μl
7010102019	10μl	10μl	0.8%	0.08μl	0.8%	0.08μl
7010102020	20μl	20μl	0.6%	0.12μl	0.5%	0.1μl
7010102021	25μl	25μl	0.5%	0.125μl	0.3%	0.075μl
7010102022	50μl	50μl	0.5%	0.25μl	0.3%	0.15μl
7010102023	100μl	100μl	0.5%	0.5μl	0.3%	0.3μl
7010102024	200μl	200μl	0.4%	0.8μl	0.2%	0.4μl
7010102025	250μl	250μl	0.4%	1.0μl	0.2%	0.5μl
7010102026	500μl	500μl	0.3%	1.5μl	0.2%	1.0μl
7010102027	1000μl	1000μl	0.3%	3.0μl	0.2%	2.0μl
7010102028	2000μl	2000μl	0.3%	6.0μl	0.15%	3.0μl
7010102029	5000μl	5000μl	0.3%	15μl	0.15%	7.5μl

Single Channel Fixed Pipette



5/10/20/100/200/1000μl

Introduction:

Manual fixed pipette is a measuring tool that moves the liquid from the original container to another container within a certain range. The unit is microliter (μl). It is characterized by precision and convenience, and is widely used in biological, chemical and other fields. Often used in the laboratory for the removal of a small amount or trace liquid, different specifications, different specifications of the pipette gun supporting the use of different sizes of the gun head.

Features:

- * In line with ergonomic design, comfortable and convenient operation.
- * High precision, precise liquid separation, according to EN/SO8655 standard calibration.
- * Digital window, easy to set the range, at a glance.
- * The low part can be autoclaved without compromising performance and comfort.
- * Calibration tools and silicone grease are included for easy servicing and calibration.
- * The internal air tightness of the product is good, stable and accurate without leakage.
- * Special suction connector design, easy to observe the sealing condition.

Technical Parameters:

Cat.No.	Volume	Measured volume	Maximum Permissible Systematic Error		Maximum Permissible Random Error	
		μl	±%	±μl	±%	±μl
10102001	5μl	5	0.4	0.02	0.4	0.02
10102002	10μl	10	0.5	0.05	1.1	0.11
10102003	20μl	20	0.5	0.1	0.4	0.08
10102004	100μl	100	0.3	0.3	0.9	0.9
10102005	200μl	200	0.3	0.6	0.1	0.2
10102006	1000μl	1000	0.3	3	0.1	1