

Bath / Circulator Thermostatic Water Tank

Features:

- * All-round heating, rapid temperature rise, constant temperature operation, making the experiment accurate.
- * OLED display, temperature, time and other parameters displayed in real time.
- * Intelligent algorithm monitoring, water shortage stops heating when turned on, and the working time of the instrument can be freely set.
- * Lid of water bath can be adapted to various sizes of containers.

Technical Parameters:

Model	BK-W2	BK-W4	BK-W6
Capacity	5L	10L	20L
Chamber	Stainless steel		
Temp. Range	RT~100°C		
Temp. Fluctuation	±0.5°C		
Display	OLED		
Timing	Yes		
Consumption	600W	1000W	1500W
Power Supply	AC220V, 50/60Hz(Standard); AC110V, 50/60Hz(Optional)		
Internal Size(W*D*H)	300*150*150mm	325*300*145mm	505*300*150mm
External Size(W*D*H)	385*280*275mm	385*420*275mm	570*420*275mm
Net Weight	6.15kg	7.85kg	11.3kg
Packing Size(W*D*H)	444*294*324mm	444*444*324mm	634*444*324mm
Gross Weight	7.8kg	10.5kg	13.6kg

Optional Tube Rack:

Model	BK-W2	BK-W4	BK-W6
Φ13mm*40	1	3	5
Φ14mm*40	1	3	5
Φ16mm*40	1	3	4
Φ17mm*40	1	3	4
Φ19mm*30	1	3	5
Φ19mm*40	1	2	4
Φ19mm*50	1	2	3
Φ21mm*12	1	4	7
Φ21mm*40	1	2	4
Φ21mm*50	1	2	3
Φ23mm*12	1	4	7
Φ23mm*40	1	2	2
Φ25mm*40	1	2	2
Φ27mm*12	1	3	6
Φ27mm*40	1	2	2
Φ30mm*12	1	3	5
Φ30mm*24	1	2	2
Φ30mm*40	1	1	1
Φ32mm*12	1	3	5
Φ32mm*24	1	2	2



Thermostatic Water Tank



Technical Parameters:

Model	WT-420	WT-24	WT-26	WT-28	WT-100
Type	1 row, 2 holes	2 rows, 4 holes	2 rows, 6 holes	2 rows, 8 holes	/
Capacity	15L	19L	30L	37L	100L
Temp. Range	RT+5~100°C(Normal atmosphere)				
Temp. Fluctuation	±0.5°C				
Temp. Uniformity	±0.5°C				
Temp. Precision	0.1°C				
Time Range	1~9999/continuous				
Consumption	1500W			1800W	2000W
Power Supply	AC220V, 50/60Hz(Standard); AC110V, 50/60Hz(Optional)				
Lid Size	Φ37, Φ58, Φ79, Φ100, Φ120				
Internal Size(W*D*H)	420*180*204mm	320*300*200mm	500*300*200mm	620*300*200mm	1330*450*170mm
External Size(W*D*H)	597*258*270mm	515*390*295mm	665*364*281mm	815*390*295mm	1501*523*288mm
Net Weight	8.8kg	11kg	15kg	16kg	40kg
Package Size(W*D*H)	650*310*330mm	570*445*360mm	710*405*330mm	870*445*360mm	1550*575*330mm
Gross Weight	11kg	13kg	18kg	19kg	45kg

Features:

- * Microprocessor control, LED display.
- * Timing function and over-temperature protection.
- * External material: Cold rolled steel with anti bacteria powder coating.
- * Inner material: Stainless steel inner chamber.

Technical Parameters:

Model	WT-42	WT-60
Capacity	13.6L	32L
Temp. Range	RT+5~100°C	
Temp. Fluctuation	±0.5°C	
Consumption	800W	1500W
Power Supply	AC110V/220V±10%, 50/60Hz	
Internal Size(W*D*H)	420*180*180mm	600*300*180mm
External Size(W*D*H)	580*250*270mm	760*310*270mm
Package Size(W*D*H)	640*310*310mm	820*440*310mm
Net Weight	10kg	15kg
Gross Weight	11kg	17kg

