



Pro Series Class II B2 Biological Safety Cabinet



LCD Display
7 inch touch screen display is easy to monitor all the safety parameters at a glance and ergonomically sized control panel improves user interface.




Work Zone
Work zone, made of 304 stainless steel, is surrounded by negative pressure.




Remote Control
All functions can be realized with it, making the operation much easier and more convenient.



Anti-paper dust structure



UV Lamp
Emission of 253.7 nanometers for most efficient decontamination.



Front Window
Two-layer laminated toughened glass≥6mm, Anti UV



Footmaster Caster
Universal caster with brake and leveling feet



Foot Switch
Adjust front window height by foot during experiment, to avoid airflow turbulence caused by arm movement.



Waterproof Socket
2 waterproof sockets are located in the side wall, for optimum convenience of using small devices inside the cabinet.



Worktop Holder Usage Diagram

ADVANTAGE

1. 7-inch large touch color display: touch operation, real-time and clearer display of various values of the safety cabinet, dynamic air flow pattern diagram, fault alarm sound and light prompt.
2. The power-on password can be set to prevent mis-operation by irrelevant personnel.
3. Automatically adjust the wind speed.
4. Power-failure memory, restore the state before power-failure, and have a visual reminder to alarm.
5. Interlocking function: UV lamp and front window; UV lamp and fan; fan and front window.
6. It has an appointment timing function, which can automatically set the timing of turning on, turning off and the running time of the UV lamp, fan, and socket.

TECHNICAL PARAMETERS

Model	BSC-1100IIB2-Pro		BSC-1500IIB2-Pro	BSC-1800IIB2-Pro
External Size(W*D*H)	1100*750*2255mm		1500*770*2290mm	1875*795*2280mm
Internal Size(W*D*H)	940*600*655mm		1350*600*660mm	1700*600*660mm
Tested Opening	Safety height 200mm(8")			
Max Opening	420mm(17")	500mm(20")	480mm(20")	
Inflow Velocity	0.53±0.025m/s			
Down Flow Velocity	0.33±0.025m/s			
ULPA Filter	Two, 99.9995% efficiency at 0.12µm, filter life indicator			
Front Window	Motorized, two-layer laminated toughened glass≥6mm, anti UV			
Noise	≤ 67dB			
UV Lamp	30W*1	40W*1	40W*1	
	UV timer, UV life indicator, emission of 253.7 nanometers for most efficient decontamination			
Illuminating Lamp	LED lamp			
	12W*2	16W*2	16W*2	
Illumination	≥1000Lux			
Consumption	800W	1300W	1400W	
Waterproof Sockets	Two, total load of two sockets: 500W			
Display	7-inch touch screen display: exhaust filter and downflow filter pressure, filter and UV lamp working time, inflow and downflow velocity, filter life, humidity and temperature, system working time, etc.			
Control System	Microprocessor			
Airflow System	0% air re-circulation, 100% air exhaust			
Alarm	Abnormal airflow velocity, Filter replacement, Front window at unsafe height, High filter pressure alarm			
Exhaust Duct	4 meters PVC duct, Diameter: 300mm			
Material	Work Zone: 304 stainless steel			
	Main Body: Cold-rolled steel with anti-bacteria powder coating			
Work Surface Height	750mm(Size can be customized according to requirements)			
Caster	Footmaster caster			
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz			
Standard Accessory	LED lamp*2, UV lamp*2, base stand, remote control, foot switch, exhaust blower, exhaust duct, drain valve, waterproof sockets*2, pipe strap*2			
Optional Accessory	1. Water and gas tap, Electric height adjustable base stand. 2. Wind speed self adjustment function, real-time compensation for wind speed through sensor monitoring. 3. APP networking remote control. 4. LED fluorescent lamp brightness adjustment function. 5. Base bracket with manual or electric height adjustment function. 6. Manual lifting front window function. 7. Manual automatic lifting front window function. 8. EC fan			
Package	Main Body	1250*980*1765mm	1640*980*1825mm	2000*1040*1895mm
	Exhaust Blower(W*D*H)	920*790*690mm	920*790*790mm	920*790*840mm
Gross Weight	265kg; 50kg		325kg; 56kg	420kg; 60kg