

Combination Emergency Shower Eye Washer



Material: Stainless steel, firm and chemical resistant.

Eye washer is suitable for cleaning eyes, face and hands; the spray head can be use of washing the whole body.

Switch of the spray shower is controlled by the top of the handle, the flow is steady and ample.

Height of the bowl is condign, couple water bores humanistic design, the heigh and angle design is according to the proportion of the face.

Outlet water bore has been handled, making the water more mild, in order to protect the eyes from being harmed.

Valve-switch make the operation simple, when using only to touch the knob.

Drain directly, the used water flow directly through the tube which is in the bowl, no pollution.

Technical Parameters:

| Model                 | SEW-C1       | SEW-C2       |
|-----------------------|--------------|--------------|
| Package Size(W*D*H)mm | 1310*380*250 | 1310*350*440 |
| Gross Weight(kg)      | 17.5         | 20           |

Fiber Analyzer

Application:

BK-F800 Fiber Analyzer is with advanced design, easy operation and flexible application. It can be used in conventional Weende method to analyze crude fiber and Van Soest analysis to wash the fiber. Applies to plant, feed, food and other agricultural products as well as the determination crude fiber, neutral detergent fiber (NDF), acid detergent fiber (ADF), hemicellulose and acid detergent lignin (ADL)

Features:

- \* Hidden solution barrel pull structure designed to facilitate dosing operation, provide the safest fiber analysis.
- \* Corrosive liquid is not in contact with any pump body, to avoid waste discharge pump susceptible to corrosion phenomena.
- \* The crucible recoil function designed to prevent sample in the crucible can not caking filtration.
- \* With dosing overflow protection function to prevent dosing corrosive liquid overflow due to operator error, protect the safety of the operator.
- \* Adjust the crucible heating power in time, enabling operator to control the heating rate easily and low down the energy consumption, ECO-friendly.
- \* Having a built-in pre-heating function, greatly reducing the whole experiment time.
- \* Provide five various specifications crucible specifications to meet the needs of different samples for standard configuration.



Technical Parameters:

| Model                | BK-F800  |
|----------------------|--|
| Measurement Range    | 0.1%~100%  |
| Sample Weight        | 0.5~3g per piece   |
| Repeatability        | ≤0.4% (Craw Fiber Content below 10%)<br>≤1% (Craw Fiber Content above 10%) |
| Max. Capacity        | 6 pcs/batch  |
| Pre-heating Time     | 10~12min   |
| Heating to Boiling   | 13~15min   |
| Consumption          | 2.2KW  |
| Power Supply         | AC220V±10%, 50Hz   |
| External Size(W*D*H) | 776*476*644mm  |
| Package Size(W*D*H)  | Main Body:680*950*840mm / Accessories:480*340*250mm                        |
| Gross Weight         | Main Body:114kg /Accessories:4.6kg   |