

Thermostatic Water Bath



SY-1L4H

SY-1L6H

Features:

- * Stainless steel inner chamber and upper cover.
- * Adopt new design structure, which could avoid the leakage of steam.
- * PID microprocessor controller, LCD display.
- * With universal fixture for SY-1L4H and SY-1L6H.

Technical Parameters:

Model	SY-1L4H	SY-1L6H
Capacity	12.6L	18.7L
Temp. Range	RT~100°C	
Temp. Precision	±1°C	
Temp. Fluctuation	±0.5°C	
Temp. Uniformity	±0.5°C	
Time Range	0-999min	
Display	LED Display	
Anti-dry Protection	Optional	
Consumption	1000W	1500W
Power Supply	AC110/220V±10%, 50/60Hz	
Internal Size(W*D*H)	610*160*130mm	900*160*130mm
External Size(W*D*H)	770*310*170mm	1100*310*170mm
Net Weight	10kg	13kg
Packing Size(W*D*H)	820*330*250mm	1150*330*250mm
Gross Weight	11kg	14.5kg

Super Thermostatic Water Bath



Introduction:

Super Thermostatic Water Bath , is made from imported corrosion-resistant plate with advanced manufacturing process, whose performance index accords with national standard requirements. It is of high precision to control temperature, strong anti corrosion, compact conformation, beautiful figure, saving energy sources, and long use life etc. It is applicable for precise constant temperature by direct or auxiliary heating in biology, physics, plants, chemicals, and environment protection etc.

Features:

- * Stainless steel inner chamber and upper cover.
- * High temperature resistance, corrosion resistance
- * External Material: cold rolled steel with powder coating.
- * PID Microprocessor controller, LED display.
- * The thermal equilibrium time is short, the temperature fluctuation is small, and the uniformity is good.

Technical Parameters:

Model	WB-501	WB-601
Capacity	20L	
Temp. Range	RT+5~100°C	
Temp. Precision	0.1°C	
Temp. Fluctuation	≤±0.1°C	
Temp. Uniformity	±0.1°C	
Timing Range	0~999min	
Display	LED	
Flow Rate of Pump	≥6L/min	
Consumption	800W	1000W
Power Supply	AC110/220V±10%, 50/60Hz	
Workroom Size(L*D*H)	280*240*180mm	
Internal Size(L*D*H)	400*280*180mm	
External Size(L*D*H)	470*360*390mm	
Net Weight	12kg	
Packing Size(L*D*H)	520*410*420mm	
Gross Weight	14kg	