

## Table Top Large Capacity Shaker



## Applications:

It is widely used in bacterial culture, fermentation, hybridization, biochemical reaction, enzyme and cell tissue research in the pharmaceutical industry. It has extensive and major applications in research and application fields such as medicine, biology, molecular science, pharmacy, food, and environment.

## Features:

- \* Ultra-low speed start function, the start speed is adjustable.
- \* Restore function after power on.
- \* Equipped with high-quality servo motor, the control speed is accurate, the high and low speed performance is good, and the stability is strong.
- \* The speed-up control circuit is adopted to start slowly and accelerate steadily to ensure the safety of experimental samples.

## Technical Parameters:

Model	SK-852	SK-872	SK-862F	SK-882F
Controller	PID			
Display	LCD			
Circulation Mode	Natural convection			
Shaking Mode	Rotatory shaking		Reciprocating shaking	
Drive Mode	Multi-dimensional driv	I drive Track drive		
Rotating Speed	20-300rpm	20-150rpm		20-260rpm
Rotating Accuracy	±1rpm			
Vibration Range	Ф26mm	0-50mm		
Timing Range	0-9999h/min			
Shaking Plate Size	800*600mm	950*730mm		800*600mm
Shaking Plate Quantity	2pcs			
Standard Capacity	250ml*46 &	250ml*71 &	250ml*71 &	250ml*46 &
(Flask Clamps Qty)	1000ml*18	1000ml*30	1000ml*30	1000ml*18
Optional Flask Clamps	250ml*96 or 500ml*66 or 1000ml*40	250ml*160 or 500ml*106 or 1000ml*60 or 2000ml*40 or 3000ml*24		250ml*96 or 500ml*66 or 1000ml*40
Optional Sticky Board	250ml*96 or 500ml*64 or 1000ml*40	250ml*142 or 500ml*106 or 1000ml*60 or 2000ml*40 or 3000ml*24		250ml*96 or 500ml*64 or 1000ml*40
External Material	Cold-rolled steel with anti-bacterial powder coating			
Consumption	200W	300W		200W
Power Supply	220V±10%, 50/60Hz (Standard); 110V±10%, 60Hz (Optional)			
External Size(W*D*H)	900*650*900mm	1040*760*1050mm		900*650*900mm
Packing Size(W*D*H)	1110*800*1155mm			
Gross Weight	350kg			

37