

## Hydrogen Generator



HG-300II

HG-500II

### Features:

- \* Easy to operate, safe and reliable, one-time add alkali, daily use only need to supplement distilled water. Turn on the power switch to produce hydrogen.
- \* The air passage part is made of stainless steel pipe. Electrolytic polishing, ultrasonic cleaning. With over - pressure protection device, two - stage purification.
- \* Unique anti-return device, to ensure that the instrument no liquid back phenomenon.
- \* Cartridge type electrolytic tank, electrolytic materials imported special precious metals, effectively improve the electrolytic efficiency, constant cell temperature, promote the service life of the electrolytic tank greatly improved.
- \* Stable output flow and automatic tracking. Purity does not decay, can be used continuously.

### Technical Parameters:

Model	HG-300II	HG-500II
Output Flow(ml/min)	0-300 ml/min	0-500 ml/min
Output Pressure	0-0.5 Mpa(Factory setting 0.4Mpa)	
Purity	> 99.999%	
Surrounding Requirement	Temperature: 10~40℃	
	Humidity: ≤85%	
Consumption	220W	
Power Supply	AC220V±10%, 50Hz±5%(Standard) AC110, 60Hz(Optional)	
Instrument Size(W*D*H)	320*180*370mm	
Package Size(W*D*H)	390*250*460mm	
Net Weight	10kg	
Gross Weight	14kg	

## Nitrogen Generator



NG-300II

NG-500II

NG-300P

NG-500P

### Features:

- \* Improved double-cathode stainless steel electrolytic separation cell. Nitrogen production by electrolysis and oxygen exhaust are carried out simultaneously, and the electrolyte circulation is unimpeded.
- \* The electrolysis separation cell has large electrolysis area, low cell temperature, large gas production, and higher nitrogen purity.
- \* The unique anti-liquid return device ensures that the instrument will never return liquid.
- \* Equipped with the function of voltage stabilization and automatic closing of the gas circuit after power failure.
- \* Adopt advanced switching power supply to improve the efficiency of electrolysis and separation.
- \* Small size and light weight, some products use oil-free compressors. (NG-300P/500P).
- \* Need external air source(NG-300II/500II).

### Technical Parameters:

Model	NG-300II	NG-500II	NG-300P	NG-500P
Output Flow(ml/min)	0-300 ml/min	0-500 ml/min	0-300 ml/min	0-500 ml/min
Output Pressure	0-0.5 Mpa(Factory setting 0.4Mpa)			
Purity	> 99.997%			
Surrounding Requirement	Temperature 10~40℃			
	Humidity ≤85%			
Consumption	80W	120W	650W	750W
Power Supply	AC220V±10%, 50Hz±5%(Standard) AC110, 60Hz(Optional)			
Instrument Size(W*D*H)	320*220*370mm		400*300*640mm	
Package Size(W*D*H)	390*280*430mm		475*375*720mm	
Net Weight	15kg		40kg	
Gross Weight	17kg		42kg	