

ABBE Digital Refractometer

Features for BK-RZT:

- * Full automatic measuring
- * Touch Screen
- * LCD temperature display, automatic correction and saving the data
- * Standard RS232 and USB interface

Features for BK-R2S:

- * Hard glass prism
- * Standard RS232 interface
- * Measure the Brix of sugar solution
- * Visual aim and LCD display
- * Automatic correcting of the effect of temperature on the Brix
- * Measuring refractive index nD of transparent or translucent liquid and solid substances.



Technical Parameters:

Model	BK-RZT	BK-R2S
Measuring Range	1.30000~1.70000nD Brix: 0-100%	1.3000~1.7000nD Brix: 0-100%
Measuring Resolution	±0.00001nD Brix: ±0.01%	±0.0001nD
Measuring Accuracy	±0.0002nD Brix: ±0.1%	±0.0002nD Brix: ±0.1%
Test Mode	8	1
Temperature Range	10~60℃	0~50℃
Temperature Resolution	0.1℃	
Temperature Accuracy	0.5℃	
Interface	RS232, USB	RS232
Display	7" LCD touch screen	LCD
Prism	Hard glass	
Power Supply	AC110/220V±10%, 50/60Hz	
External Size(W*D*H)	340*200*110mm	210*110*310mm
Package Size(W*D*H)	500*330*220mm	370*240*470mm
Gross Weight	9kg	12kg

Automatic Digital Refractometer



Features:

- * Multiple measurement modes: refractive index of spice and plant oil, F42 and F55 fructose syrup, concentration of glucose and sucrose, solid content, water content of honey, nD20, etc.
- * It meets graded management, provides scientific and user-friendly operation.
- * Fast measurement, only needs a small amount of samples.
- * Accurate detection and thermostatic control.
- * Prism is made of sapphire.

Technical Parameters:

Model	BK-R756	
Measuring Range	nD: 1.30000~1.70000	
	Brix: 0~100%	
Measuring Accuracy	Refractive index nD: ±0.0002	
	Brix: ±0.1%	
Measuring Resolution	Refractive index nD:±0.00001	
	Brix:±0.01%	
Temperature	Temperature display range : 0~100℃	
Audit Trail	Optional(FDA)	
Thermostatical Control Range	5~85°C	
Temperature Control Accuracy	±0.02℃	
Temperature Control Mode	Peltier (Built-in)	
Interface	USB/Keyboard/Mouse/Universal Printer/	
	Ethernet/Optional:WLAN	
Display	8 inch color touch screen	
Data Storage	16G	
Prism	Artifical sapphire	
Power Supply	100V~240V, 50/60Hz, 150W	
Gross Weight	5kg	
Package Size	570*460*300mm	

385