Automated Tissue Processor



Features:

- * 5.5-inch large LCD touch screen, real-time display of equipment working status.

 * Automatic drying function, intelligent control of hot air system, good drying effect, energy saving and durability.

 * The dyeing processing method can be customized, which can meet the requirements of various dyeing methods, various users, and various specimens.

 * Fully enclosed structure, environmentally friendly efflux air purification system, efficient treatment of toxic and harmful

Technical Parameters:

Model = mail	BK-TS1B (a) DIODASE COM
Cup Number	12pcs (9pcs reagent cup, 3pcs paraffin cup)
Tissue Protective Cup	1~7th cup can be set
Single Cup Capacity	1100ml
Single Cup Processing Time	1st cup:0~99h59min; other cups:0~23h59min
Agitation Frequency	0~6 times/min, adjustable
Dripping Time	0~59s, adjustable
Processing Basket Capacity	50pcs of dehydration cassette
Program Storage	8 sets
Noise	60dB(A)
Power	600W
Power Supply	AC220V,50/60Hz(Standard); AC110V, 60Hz(Optional)
External Size(W*D*H)	1020*410*450mm
Package Size(W*D*H)	1130*560*640mm
Net Weight	63kg
Gross Weight	88kg



- Features:

 * 5.5-inch large LCD touch screen, real-time display of the device working status

 * Rich man-machine dialogue interface, with online help function, easy to learn

 * Tank surface dripping time can be adjusted, reduce the chance of channeling, prolong the use of reagents, reduce pollution
- * Manual operation can be inserted at will, and automatically enter the original running state, convenient to check or add specimens during operation

Technical Parameters:

Model	BK-TS2B (0) DIO DASA COM
Cup Number	12pcs (9pcs reagent cup, 3pcs paraffin cup)
Tissue Protective Cup	1~7th cup can be set
Single Cup Capacity	1800ml
Single Cup Processing Time	1st cup:0~99h59min; other cups:0~23h59min
Agitation Frequency	0-6times/min, adjustable
Dripping Time	0-59s, adjustable
Processing Basket Capacity	100pcs of dehydration cassette
Program Storage	8 sets
Noise	60dB(A)
Power	600W
Power Supply	AC220V,50/60Hz(Standard); AC110V, 60Hz(Optional)
External Size(W*D*H)	1135*465*490mm
Package Size(W*D*H)	1260*580*690mm
Net Weight	78kg
Gross Weight	102kg

387 388