

Tissue Embedding Center

Features:

- * Fully automatic program control, can be preset to start any day within a week.
- * The temperature control adopts a single-chip microprocessor controller, and the temperature setting is simple.
- * Using a new type of heating element, the heating is fast, the heating is uniform, and the energy saving is reliable.
- * Equipped with a small cooling platform, the base mold paraffin can be quickly pre-cooled.



Technical Parameters:

| Model | BK-TEI |
|-------------------------------|---|
| Thermal Temperature Range | RT~80°C |
| Control Temperature Precision | ±3°C |
| Timing Range | 0~24h |
| Paraffin Chamber Size | 350*145*80mm |
| Thermal Storage Size | 205*145*60mm, two pcs |
| Working Area Size | 500*145mm |
| Power | 1100W |
| Power Supply | AC220V, 50/60Hz(Standard); AC110V, 60Hz(Optional, external transformer) |
| External Size(W*D*H) | 525*550*500mm |
| Net Weight | 36kg |
| Packing Size(W*D*H) | 650*660*660mm |
| Gross Weight | 43kg |

Tissue Cooling Center

Features:

- * Environmentally friendly fluorine-free refrigerant is selected, with low noise and fast cooling effect.
- * The temperature control adopts a single-chip microprocessor controller, and the temperature setting is simple.
- * With temperature control mode and super cooling mode, high temperature control accuracy.
- * The cooling temperature can be adjusted to achieve the ideal cooling effect.



Technical Parameters:

| Model | BK-CPIV |
|-------------------------------|---|
| Temperature Control Range | 5 to -20°C(Max to -28°C) |
| Control Temperature Precision | ±3°C |
| Working Area Size | 360*300mm |
| Number of Embedding Cassettes | 90pcs |
| Power | 300W |
| Power Supply | AC220V, 50/60Hz(Standard); AC110V, 60Hz(Optional, external transformer) |
| External Size(W*D*H) | 350*630*400mm |
| Net Weight | 23kg |
| Packing Size(W*D*H) | 500*800*590mm |
| Gross Weight | 43kg |

Remark: The above two products should be used together.

Tissue Embedding Center

Features:

- * 7-inch high-definition touch screen for easy operation and clear, accurate display.
- * Fully automatic program control supports scheduled power-on any day within one week.
- * Temperature control via single-chip microprocessor controller for simple parameter setting.
- * New heating element ensures fast heating, uniform temperature distribution, energy efficiency and reliability.



Technical Parameters:

| Model | BK-TEII |
|--------------------------------|---|
| ModelThermal Temperature Range | RT~80°C |
| Control Temperature Precision | ±3°C |
| Timing Range | 0~24h |
| Paraffin Chamber Size | 445*125*115mm |
| Thermal Storage Size | 205*153*57mm, two pcs |
| Working Area Size | 500*70mm |
| Pre-Cooling Table Size | 60*70mm |
| Power | ≤1100W |
| Power Supply | AC220V, 50/60Hz(Standard); AC110V, 60Hz(Optional, external transformer) |
| External Size(W*D*H) | 525*590*450mm |
| Net Weight | 38kg |
| Packing Size(W*D*H) | 650*700*660mm |
| Gross Weight | 46kg |

Tissue Cooling Center

Features:

- * Environmentally friendly fluorine-free refrigerant is selected, with low noise and fast cooling effect.
- * The temperature control adopts a single-chip microprocessor controller, and the temperature setting is simple.
- * With temperature control mode and super cooling mode, high temperature control accuracy.
- * The cooling temperature can be adjusted to achieve the ideal cooling effect.



Technical Parameters:

| Model | BK-CPII |
|-------------------------------|---|
| Temperature Control Range | 5 to -20°C(Max to -28°C) |
| Control Temperature Precision | ±3°C |
| Working Area Size | 320*310mm |
| Number of Embedding Cassettes | 80pcs |
| Power | 300W |
| Power Supply | AC220V, 50/60Hz(Standard); AC110V, 60Hz(Optional, external transformer) |
| External Size(W*D*H) | 350*560*435mm |
| Net Weight | 23kg |
| Packing Size(W*D*H) | 480*660*590mm |
| Gross Weight | 40kg |

Remark: The above two products should be used together.