

## Tissue Embedding Center

### Features:

- \* 7-inch high-definition touch screen for easy operation and clear, accurate display.
- \* Fully automatic program control supports scheduled power-on any day within one week.
- \* Temperature control via single-chip microprocessor controller for simple parameter setting.
- \* New heating element ensures fast heating, uniform temperature distribution, energy efficiency and reliability.



### Technical Parameters:

Model	BK-TEII
Model Thermal Temperature Range	RT~80°C
Control Temperature Precision	±3°C
Timing Range	0~24h
Paraffin Chamber Size	450*150*90mm
Thermal Storage Size	205*153*57mm, two pcs
Working Area Size	500*70mm
Pre-Cooling Table Size	60*70mm
Power	≤1100W
Power Supply	AC220V, 50/60Hz(Standard); AC110V, 60Hz(Optional)
External Size(W*D*H)	525*550*450mm
Net Weight	36kg
Packing Size(W*D*H)	650*660*660mm
Gross Weight	43kg

## Tissue Cooling Center

### Features:

- \* Environmentally friendly fluorine-free refrigerant is selected, with low noise and fast cooling effect.
- \* The temperature control adopts a single-chip microprocessor controller, and the temperature setting is simple.
- \* With temperature control mode and super cooling mode, high temperature control accuracy.
- \* The cooling temperature can be adjusted to achieve the ideal cooling effect.



### Technical Parameters:

Model	BK-CPII
Temperature Control Range	5 to -20°C(Max to -28°C)
Control Temperature Precision	±3°C
Working Area Size	320*310mm
Number of Embedding Cassettes	80pcs
Power	300W
Power Supply	AC220V, 50/60Hz(Standard); AC110V, 60Hz(Optional)
External Size(W*D*H)	350*560*435mm
Net Weight	23kg
Packing Size(W*D*H)	480*770*590mm
Gross Weight	40kg

Remark: The above two products should be used together.

## Tissue Embedding Center

### Features:

- \* Fully automatic program control; power-on can be preset for any day within a week.
- \* Temperature controlled by a single-chip microprocessor for simple and convenient setting.
- \* Equipped with new heating elements for fast heating, uniform temperature distribution, energy efficiency and reliability.
- \* Fitted with a flexible metal hose magnifier, ideal for manipulating tiny specimen tissues.
- \* 7-inch HD touch screen for easy, intuitive operation and clear, accurate display.



### Technical Parameters:

Model	BK-TEV
Thermal Temperature Range	RT~80°C
Control Temperature Precision	±3°C
Timing Range	0~24h
Paraffin Chamber Size	650*130*97mm
Thermal Storage Size	240*240*57mm, two pcs
Working Area Size	700*93mm
Pre-Cooling Table Size	69*59mm
Power	≤1400W
Power Supply	AC220V, 50/60Hz(Standard); AC110V, 60Hz(Optional)
External Size(W*D*H)	735*693*413mm
Net Weight	45kg
Packing Size(W*D*H)	880*850*650mm
Gross Weight	72kg

## Tissue Cooling Center

### Features:

- \* Environmentally friendly fluorine-free refrigerant is selected, with low noise and fast cooling effect.
- \* The temperature control adopts a single-chip microprocessor controller, and the temperature setting is simple.
- \* With temperature control mode and super cooling mode, high temperature control accuracy.
- \* The cooling temperature can be adjusted to achieve the ideal cooling effect.



### Technical Parameters:

Model	BK-CPV
Temperature Control Range	5 to -20°C(Max to -28°C)
Control Temperature Precision	±3°C
Working Area Size	370*310mm
Number of Embedding Cassettes	90pcs
Power	300W
Power Supply	AC220V, 50/60Hz(Standard); AC110V, 60Hz(Optional)
External Size(W*D*H)	350*630*410mm
Net Weight	23kg
Packing Size(W*D*H)	480*770*590mm
Gross Weight	40kg

Remark: The above two products should be used together.