

-60°C Freezer



BDF-60V30



BDF-60V58



BDF-60V108



BDF-60V158



BDF-60V398

Technical Parameters

Model	BDF-60V30	BDF-60V58	BDF-60V108	BDF-60V158	BDF-60V398
Capacity	28L	58L	108L	158L	408L
Temp. Range	-25~-60°C				
Temp. Accuracy	0.1°C				
Temp. Uniformity	±2°C				
Temp. Stability	±2°C				
Control System	Microprocessor control				
Display	LED display				
Alarm	High and low temperature alarm, thermostat fault alarm				
Refrigeration Type	Direct-cooling				
Refrigerant	R404A/R23 110g	R404A/R23 130g	R404A/R23 220g	R404A/R23 220g	R404A/R23 380g
Compressor	International famous brand compressor /1				
Condenser & Evaporator	Copper tube aluminum fin condenser; cabinet-wrapped copper tube evaporator				
Defrost	Manual defrost				
Construction	Polyurethane cyclopentane foam				
Material	Internal Material	304 stainless steel			
	External Material	Sprayed steel plate			
Door	Outer door: sprayed steel plate outer door*1		Outer door: sprayed steel plate outer door*1	Outer door: sprayed steel plate outer door*1	Outer door: sprayed steel plate outer door*1
	Interior door: 304 stainless steel door*1		Interior door: 304 stainless steel door*2	Interior door: 304 stainless steel door*2	Interior door: 304 stainless steel door*4
Consumption	370W	380W	400W	400W	800W
Power Supply	AC 220V, 50Hz(Standard); 110/220V, 60Hz(Optional)				
Casters	Yes				
Shelf	1			2	3
Standard Accessory	Test hole				
Optional Accessory	Temperature recorder				
Internal Size (W*D*H)	270*265*400mm	364*405*410mm	460*460*510mm	460*460*510mm	610*615*1120mm
External Size (W*D*H)	505*520*1165mm	540*620*1115mm	700*730*1260mm	700*730*1260mm	850*900*1780mm
Package Size (W*D*H)	Plywood: 535*575*1290mm	Plywood: 670*760*1290mm	Plywood: 765*815*1395mm	Plywood: 765*815*1395mm	980*980*1930mm
	Honeycomb cardboard box: 595*640*1335mm	Honeycomb cardboard box: 590*785*1320mm	Honeycomb cardboard box: 790*850*1430mm	Honeycomb cardboard box: 790*850*1430mm	
Net Weight	71kg	78kg	107kg	107kg	188kg
Gross Weight	90kg	98kg	133kg	133kg	238kg