

-60°C Freezer



Technical Parameters

Model	BDF-60V30	BDF-60V58	BDF-60V108	BDF-60V158	BDF-60V398
Capacity	28L	58L	108L	158L	408L
Temp. Range	-25~-60°C				
Temp. Accuracy	0.1°C				
Temp. Uniformity	±2°C				
Temp. Stability	±2°C				
Control System	Microprocessor control				
Display	LED display				
Alarm	High/low temperature alarm, controller failure alarm				
Refrigeration Type	Direct-cooling				
Refrigerant	R404A/R23 110g	R404A/R23 130g	R404A/R23 220g	R404A/R23 240g	R404A/R23 380g
Compressor	International famous brand compressor /1				
Condenser & Evaporator	Copper tube aluminum fin condenser; cabinet-wrapped copper tube evaporator				
Defrost	Manual defrost				
Construction	Polyurethane cyclopentane foam				
Material	Internal Material 304 stainless steel				
	External Material Sprayed steel plate				
Door	Outer door: sprayed steel plate outer door*1				
	Interior door: 304 stainless steel door*1				
Consumption	370W	380W	400W	450W	800W
Power Supply	AC 220V, 50Hz(Standard); 110/220V, 60Hz(Optional)				
Casters	Yes				
Shelf	1		2		3
Standard Accessory	Test hole				
Optional Accessory	Temperature recorder				
Internal Size (W*D*H)	270*265*400mm	364*405*410mm	460*460*510mm	460*455*800mm	610*615*1120mm
External Size (W*D*H)	505*520*1165mm	540*620*1115mm	700*730*1260mm	700*700*1580mm	850*900*1780mm
Package Size (W*D*H)	535*575*1290mm	670*760*1290mm	765*815*1395mm	760*790*1720mm	980*980*1930mm
Net Weight	71kg	78kg	107kg	123kg	188kg
Gross Weight	90kg	98kg	133kg	150kg	238kg

-60°C Freezer



Technical Parameters

Model	BDF-60V608	BDF-60V708	BDF-60V808	BDF-60V938
Capacity	608L	708L	808L	938L
Temp. Range	-25~-60°C			
Temp. Accuracy	0.1°C			
Temp. Uniformity	±4°C			
Temp. Stability	±4°C			
Control System	Microprocessor control			
Display	LED display			
Alarm	High/low temperature alarm, controller failure alarm			
Refrigeration Type	Direct-cooling			
Refrigerant	R404A/R23 480g	R404A/R23 520g	R404A/R23 580g	R404A/R23 610g
Compressor	International famous brand compressor /2(Dual independent refrigeration system)			
Condenser & Evaporator	Copper tube aluminum fin condenser; cabinet-wrapped copper tube evaporator			
Defrost	Manual defrost			
Construction	Polyurethane cyclopentane foam			
Material	Internal Material 304 stainless steel			
	External Material Sprayed steel plate			
Door	Outer door: sprayed steel plate outer door*1			
	Interior door: 304 stainless steel door*4			
Consumption	900W	1050W	1100W	1100W
Power Supply	AC 220V, 50Hz(Standard); 110/220V, 60Hz(Optional)			
Casters	Yes			
Shelf	3			
Standard Accessory	Test hole			
Optional Accessory	Temperature recorder			
Internal Size (W*D*H)	750*715*1200mm	890*715*1200mm	850*725*1335mm	1040*715*1320mm
External Size (W*D*H)	990*1030*1860mm	1130*1030*1860mm	1090*1010*2000mm	1280*1030*1980mm
Package Size (W*D*H)	1120*1080*2010mm	1280*1080*2150mm	1280*1080*2150mm	1410*1080*2130mm
Net Weight	245kg	285kg	300kg	320kg
Gross Weight	288kg	345kg	370kg	405kg