

## Blood Bank Instrument Blood Collection Chair

### Features:

- \* Manual or electric control type for your choice.
- \* Made of high-strength fiber material and poly-layer paint, more durable, easy to clean.
- \* Designed with people-oriented idea, to meet the donor's sense of security and comfort, to alleviate the psychological pressure, to ensure an easier and enjoyable process.
- \* Mattress using a high-quality medical polyurethane foam molding leather, easy for clean and maintenance, anti-static and anti-fouling properties superior to other similar products.



### Technical Parameters:

Model	BK-BC100	BK-BC100A
Seat Section Size(mm)	1800*580	
Seat Section Height(mm)	480	
Backing Board Turning Angle	0~70°	
Chair Backward and Forward Tilt Angle	8°~15°	
Leg Plate Turning Angle	0~90°	
Handrail Swing Out Angle	0°~45°	
Handrail's Moving Distance	100mm	
Handrail Board Size	500*160mm	
Lifting Speed	/	3~25mm/s
Power Supply	/	AC110/220V±10%, 50/60Hz
Reading Lamp Power	/	60W
Standard Accessories	Hand operation, handrail rack, small table	
Optional Accessories	LED hose-type reading lamp; movable assistant desk; soft velvet cover	
Load Capacity	220kg	
Packing Size(W*D*H)	1500*780*600mm	
Gross Weight	65kg	75kg

## Blood Collection Monitor



### Introduction:

Blood collection monitor has the functions of weighing, zero point calibration, fluid collection control, oscillation and so on. It is an ideal equipment for blood collection, which is suitable for blood centers, blood stations, hospitals and other blood collection and supply units.

### Features:

- \* Microcomputer control is adopted to realize the integration of weighing and collecting liquid.
- \* Built-in large capacity lithium battery, long battery life.
- \* With automatic sound and light alarm function, when the amount of liquid reaches the predetermined value or the predetermined time, the alarm prompts.
- \* The gentle swing mode is safer for platelets and red blood cells that are easily damaged in the blood.
- \* Using new type of weighing sensor, weighing more accurate.
- \* Constant speed motor, low noise, long service life.
- \* The liquid collection digital display is displayed in milliliters without calculation and conversion, which is more convenient and convenient to use.

### Technical Parameters:

Model	BCM-4	BCM-12Z
Measuring Range	0~1200ml	0~1200ml
Display	LED	3.5-inch color LCD touch screen
Resolution	1ml	
Liquid Proportion	1.05g/ml	
Collection Speed	0.5-3ml/s	
Static Error	±2g	
Swing Angle	13±2°	
Swing Frequency	30±2r/min	
Alarm	Collection finish, Automatic sound and light dual alarm	Collection finish, Automatic sound and light dual alarm; Clamp obstruction
Obstruct Pipeline	/	Outer diameter φ3 ~ φ6mm, wall thickness: 0.5mm
Obstruct Resistance	/	<14N
Ambient Temperature	5°C~40°C	
Battery	Lithium battery, 12V, 5000mAh, 3 hours of battery life	/
Consumption	17W	30W
Power Supply	100~240V, 50/60Hz	
External Size(W*D*H)	190*240*165mm	285*240*190mm
Net Weight	2.5kg	3.5kg
Packing Size(W*D*H)	380*260*290mm	
Gross Weight	3.5kg	5.5kg