

## Stacked Large Capacity Shaking Incubator



BIOBASE  
E-mail: export@biobase.com  
www.biobase.com

### Introduction:

The Stacked Large Capacity Shaking Incubator is a high-performance device designed for large-scale cell culture, microbial fermentation, and other temperature-sensitive shaking applications. With its stacked design, this incubator maximizes space efficiency in laboratories while offering increased capacity for simultaneous experiments.

### Features:

- \* Brushless DC motor, low noise, lasting operation.
- \* 5"touch screen, clear and intuitive interface.
- \* Run parameter encryption lock, parameter memory function.
- \* With power failure recovery function.
- \* Motor overheat, temperature control, abnormal over temperature instrument automatically cut off their power supply.
- \* With USB data export function to achieve data traceability.
- \* With ultraviolet disinfection function.
- \* Standard equipped with LED light, open the door of the box light automatically open.

### Technical Parameters:

Model	BJPX-SDT10	BJPX-SDT20
Capacity (L)	80	
Temp. sensor	PT100	
Temp. Range	RT+5~60°C	4~60°C
Temp. Fluctuation	≤±0.5°C	
Temp. Uniformity	≤±1°C(37°C)	
Temp. Precision	0.1°C	
Timing Range	0~999min	
Controller	PID	
Display	5-inch touch screen	
Circulation Mode	Forced convection	
Shaking Mode	Rotary shaking	
Drive Mode	Single axis balanced drive type	
Vibration Range	Φ26mm	
Rotating Speed	30~300r/min	
Rotating Accuracy	±1r/min	
Shaking Plate Size	420*400mm	
Shaking Plate Quantity	1pc	
Max. Capacity	250ml*16 or 500ml*9 or 1000ml*9 or 2000ml*5(Flask clamp) Tube rack*2 96-well plate*8 Clamping rod shaking plate*1	
Standard. Capacity	500ml*9	
Lighting Mode	LED lamp*1	
Sterilization Mode	UV lamp*1	
Refrigerant	/	R290
Ambient Temp.	15~35°C	
Internal Material	304 stainless steel	
External Material	Cold rolled steel sheet	
Safety Function	High/low temperature, abnormal shutdown, motor failure, equipment door is not closed properly automatic alarm, alarm mode is sound and light alarm	
Consumption	1000W	1600W
Power Supply	Standard: AC200~240V, 50/60Hz Optional: AC110V, 50/60Hz	
Internal Size	495*455*370mm(per unit)	
External Size	580*830*600mm(per unit)	
Package Size	705*975*865mm(per unit)	
Net Weight	138kg(per unit)	158kg(per unit)
Gross Weight	168kg(per unit)	188kg(per unit)