

Tissue Flotation Water Bath &Slide Dryer



Applications:

It is suitable for medical diagnosis, biological research, epidemic prevention, forensic identification.

Features:

- * Integrating spreading, baking and roasting slices in one, compact structure (small space occupation), novel shape and easy operation.
- * The slide drying chamber can dry the slide at a constant temperature and can accommodate 3 drying racks.
- * The louver-style grilling table has a large capacity(60 slides are actually arranged), easy to put and take out, and the grilling effect is better.
- * High-brightness LCD display, real-time display of sheet spreading and drying sheet temperature, simple and clear.
- * Highly sensitive temperature control integrated unit, high precision and reliable performance.
- * With over-temperature alarm function.
- * Using new heating software, fast heating, uniform heating, small thermal inertia, reliable energy saving.
- * With memory function, automatically retain the set temperature after operation.
- * The work surface is spray-coated, corrosion-resistant.

Technical Parameters:

Model	BTH-VI
Temperature Range	RT~99℃
Temperature Precision	±1℃
Over Temperature Alarm Range	1~5℃
Water Tank Size	220*150mm*65mm
Drying Plate Size	260*150mm
Oven Size	200*100*110mm
Power	≤680W
Power Supply	AC220V,50/60Hz(Standard); AC110V, 60Hz(Optional)
External Size(W*D*H)	590*340*225mm
Package Size(W*D*H)	690*430*260mm
Net Weight	9.2kg
Gross Weight	13.5kg

Features:

- * It integrates spreading and drying, compact structure (small footprint), novel shape and easy operation.
- * The louver-type drying table has a large capacity (actually arranges 60 slides), is easy to put and take out, and has a better drying effect.
- * High-Definition digital display, real-time display of sheet spreading and drying sheet temperature, simple and clear.
- * Highly sensitive temperature control integrated unit, high precision and reliable performance.
- * With over-temperature alarm function.
- * Using new heating software, fast heating, uniform heating, small thermal inertia, reliable energy saving.
- * With memory function, automatically retain the set temperature after operation.
- * The work surface is spray-coated, corrosion-resistant.

Technical Parameters:

Model	BTH-V
Temperature Range	RT~99℃
Temperature Precision	±1℃
Over Temperature Alarm Range	1~5℃
Water Tank Size	220*150*65mm
Drying Plate Size	260*150mm
Power	≤450W
Power Supply	AC220V,50/60Hz(Standard); AC110V, 60Hz(Optional)
External Size(W*D*H)	500*330*140mm
Package Size(W*D*H)	580*420*210mm
Net Weight	8.5kg
Gross Weight	12kg

Features:

- * Integrate tissue flotation water bath and slide dryer, compact structure and easy operation
- * High-Definition digital display, real-time display of temperature.
- * Highly sensitive temperature control integrated unit, high precision and reliable performance.
- * With over-temperature alarm function
- * Using new heating materials, heating fast, uniform heating, low thermal inertia, energy saving and reliable.
- * With memory function. The set temperature is automatically retained.
- * Louver-type drying table, easy to operate, better drying effect
- * The work surface is sprayed for corrosion resistance.

Technical Parameters:

Model	BTH-I	BTH-III
Temp. Range	RT~99℃	
Temp. Precision	±1℃	
Environmental Temp. Range	0~40℃	
Over-Temp. Alarm Range	1~5℃	
Drying Area	344*260mm	
Bath Tank Size(W*D*H)	304*207*52mm	308*211*64mm(Removable)
Display	LED	
Power Supply	AC220V,50/60Hz(Standard); AC110V, 60Hz(Optional)	
Consumption	600W	
External Size(W*D*H)	695*400*210mm	
Package Size(W*D*H)	780*490*300mm	
Net Weight	15kg	
Gross Weight	20kg	

