

Tissue Flotation Water Bath



BT-I



BT-III

Features:

- * High-Definition digital display, real-time display of temperature.
- * Highly sensitive temperature control integrated unit, high precision and reliable performance.
- * With over-temperature alarm function
- * Using new heating materials, heating fast, uniform heating, low thermal inertia, energy saving and reliable.
- * With memory function. The set temperature is automatically retained.
- * The work surface is sprayed for corrosion resistance.

Technical Parameters:

Model	BT-I	BT-III
Temp. Range	RT~99℃	
Temp. Precision	±1℃	
Over-temp. Alarm Range	1~5℃	
Environmental Temp. Range	0~40℃	
Bath tank Size(W*D*H)	240*180*55mm	264*180*60mm(Removable)
Display	LED	
Power Supply	AC220V±10%, 50/60Hz(Standard); AC110V±10%, 60Hz(Optional)	
Consumption	200W	
External Size(W*D*H)	345*340*130mm	
Package Size(W*D*H)	410*410*200mm	
Net Weight	5kg	4kg
Gross Weight	7.5kg	7kg

Slide Dryer (Hot Plate)



BH-I



BH-II

Features:

- * High-Definition digital display, real-time display of temperature.
- * Highly sensitive temperature control integrated unit, high precision and reliable performance.
- * With over-temperature alarm function
- * Using new heating materials, heating fast, uniform heating, low thermal inertia, energy saving and reliable.
- * With memory function. The set temperature is automatically retained.
- * The work surface is sprayed for corrosion resistance.
- * Louver table, 65°inclination Angle, large capacity. (Only for BH-II)

Technical Parameters:

Model	BH-I	BH-II
Temp. Range	RT~99℃	
Temp. Precision	±1℃	
Environmental Temp. Range	0~40℃	
Over-temp. Alarm Range	1~5℃	
Drying Area	345*260mm	
Number of Slides	40	65
Display	LED	
Power Supply	AC220V±10%, 50/60Hz(Standard); AC110V±10%, 60Hz(Optional)	
Consumption	200W	
External Size(W*D*H)	345*340*130mm	
Package Size(W*D*H)	410*410*200mm	
Net Weight	5kg	
Gross Weight	7.5kg	