

Blood and Fluid Warmer



BK-TW201



BK-TW101



BK-TW102

Introduction:

By heating the continuous flow of liquid, the heat in the heat exchanger is transferred to the liquid in the pipe through the extended infusion pipeline to achieve the purpose of heating the liquid. The product is not in contact with the liquid. It is not used for the heating of analgesics, chemotherapy drugs, insulin and other drugs.

Features:

- * The temperature accuracy of instrument is $\pm 0.1^{\circ}\text{C}$
- * Preheating time is less than 2 minutes, rapid heating reduces waiting time
- * With door opening alarm, high and low temperature alarm devices that trigger when the monitored temperature deviates by 0.5°C from the set point, with a flashing alarm light and an accompanying beep signal (BK-TW102)
- * With high temperature alarm, low temperature alarm, system error alarm, overtime alarm, heating prompts (BK-TW101/201)
- * The protection level against water intrusion is IPX I type, water drops falling vertically have no harmful effects
- * With dual hardware and software triple temperature protection, ensuring safe use of the equipment
- * The heating instrument operates at a noise level of $\leq 65\text{dB(A)}$ during normal operation
- * Two temperature units are available, which can be switched between degrees Celsius and degrees Fahrenheit
- * Medical-grade heating silicone tubes ensure safe use, wrapping the entire pipeline to deliver effective temperature directly to the patient, with a variety of tube diameters and lengths available for selection (BK-TW101/201)

Technical Parameters:

| Model | BK-TW201 | BK-TW101 | BK-TW102 |
|-------------------------|---------------------------|-------------|--|
| Display | LCD display | | LED display |
| Temp. Range | 32~42°C | | RT+5~45°C |
| Temp. Resolution | 0.1°C | | |
| Temp. Fluctuation | $\pm 0.5^{\circ}\text{C}$ | | |
| Temp. Uniformity | / | | $\pm 1.0^{\circ}\text{C}$ |
| Preheating Time | $\leq 2\text{min}$ | | $\leq 2\text{min}$ (From $25\pm 2^{\circ}\text{C}$ to 35°C) |
| Environment Temperature | 5~40°C | | 5~30°C |
| Temp. Error | $\pm 0.5^{\circ}\text{C}$ | | $\pm 1.0^{\circ}\text{C}$ |
| Timing Range | 0~99h/Continuous | | |
| Consumption | 180W | 120W | 85W |
| Power Supply | AC100~240V, 50/60Hz | | |
| External Size (W*D*H) | 104*45*170mm | 94*45*170mm | 77*35*177mm |
| Packing Size (W*D*H) | 355*260*230mm | | 250*205*100mm |
| Net Weight | 0.8kg | 0.7kg | 0.5kg |
| Gross Weight | 2.0kg | 1.9kg | 1.1kg |



BK-TW110



BK-TW210

Introduction:

This product is primarily used for warming and maintaining the temperature of fluids (Excluding analgesics, chemotherapy drugs and insulin) administered to the human body. (Non-contact with blood or medication)

Features:

- * BK-TW110 is single-channel blood and fluid warmer, BK-TW210 is dual-channel blood and fluid warmer.
- * Dry heating method, short preheating time, rapid heating.
- * High-quality heating tube assembly, full-wrapped heating, fast heating in cold environment.
- * Heating tube assembly is plug-and-play, convenient and fast.
- * Directly heat conventional blood transfusion and infusion lines, no special consumables required, cost saving.
- * Real-time display of set temperature, real-time temperature, alarm information, working status, etc.
- * With over temperature alarm, under temperature alarm, no liquid alarm function.

Technical Parameters:

| Model | BK-TW110 | BK-TW210 |
|--------------------------------|---|---------------|
| Channel Count | Single-channel | Dual-channel |
| Adjustable Temp. Range | 32.0~42.0°C | |
| Temp. Accuracy | 0.1°C | |
| Preheating Time | $\leq 2\text{min}$ (From 20°C to 36°C) | |
| Display | LED | |
| Display Information | Heating time, set temperature, heating temperature, alarm information indication | |
| Inner Diameter of Heating Tube | Standard: 3.5~5mm Optional: 6~7mm | |
| Safety Control | The system has built-in alarm test function, and the alarm function can be tested on the panel to see if it is normal | |
| Over-temperature Alarm | An alarm will sound if the actual temperature of the heating pipe exceeds the preset temperature by 2°C | |
| Under-temperature Alarm | An alarm will sound if the actual temperature of the heating pipe falls below the preset temperature by 3°C . | |
| Heating Tube Structure | Three-cavity silicone flexible heating sleeve, integrated with 4 sets of heating wires, two sets of independent temperature sensors | |
| Power | 60VA | 80VA |
| Power Supply | AC 100~240V, 50~60Hz | |
| External Size (W*D*H) | 172*95*175mm | 195*115*175mm |
| Packing Size (W*D*H) | 250*220*230mm | |
| Net Weight | 1.7kg | 2.3kg |
| Gross Weight | 2.1kg | 2.7kg |