

Thermo Shaker



Features:

- * 7.0-inch LCD display, which shows real-time information such as current temperature, speed and time.
- * Double-layer heating system, precisely controlled at RT+5°C to 80°C.
- * The microprocessor control ensures excellent temperature stability and uniformity.
- * Speed range: 200~1800 rpm. Driven by a DC brushless motor, with stable speed.
- * It can accommodate two standard microplates, allowing for effective mixing and incubation of small samples.
- * The working time can be set arbitrarily within the range of 1min~99h59min. Once the program finishes running, the alarm signal will be issued.

Technical Parameters:

Model	BK-MDT2
Speed Range	200~1800rpm
Shaking Amplitude	3mm
Temperature Control Range	Rt+5~80°C
Thermal Cover	Yes
Temperature Uniformity	≤±0.5°C
Temperature Accuracy	≤±0.5°C
Heating Up Time	≤10min(25°C~80°C)
Timing Range	1min~99h59min
Sample Processing Volume	2 standard microplates
Display	7.0-inch touch screen display
Consumption	200W
Power Supply	AC110/220V±10%, 50/60Hz
External Dimension(W*D*H)	345*285*207mm
Net Weight	7.4kg
Packing Size(W*D*H)	544*339*249mm
Gross Weight	8.2kg

BIOBASE

E-mail: export@biobase.com
www.biobase.cc / www.biobase.com