

-60°C Freezer



Technical Parameters

Model	BDF-60V608		BDF-60V708	BDF-60V808	BDF-60V938
Capacity	608L		708L	808L	938L
Temp. Range	-25~−60°C				
Temp. Accuracy	0.1°C				
Temp. Uniformity	±4°C				
Temp. Stability	±4°C				
Control System	Microprocessor control				
Display	LED display				
Alarm	High and low temperature alarm, thermostat fault alarm				
Refrigeration Type	Direct-cooling				
Refrigerant	R404A/R23 480g	R404A/R23 520g	R404A/R23 580g	R404A/R23 610g	
Compressor	International famous brand compressor /2(Dual independent refrigeration system)				
Condenser & Evaporator	Copper tube aluminum fin condenser; cabinet-wrapped copper tube evaporator				
Defrost	Manual defrost				
Construction	Polyurethane cyclopentane foam				
Material	Internal Material	304 stainless steel			
	External Material	Sprayed steel plate			
Door	Outer door: sprayed steel plate outer door*1 Interior door: 304 stainless steel door*4				
Consumption	900W	1050W	1100W	1100W	
Power Supply	AC 220V, 50Hz(Standard); 110/220V, 60Hz(Optional)				
Casters	Yes				
Shelf	3				
Standard Accessory	Test hole				
Optional Accessory	Temperature recorder				
Internal Size (W*D*H)	750*715*1200mm	890*715*1200mm	850*725*1335mm	1040*715*1320mm	
External Size (W*D*H)	990*1030*1860mm	1130*1030*1860mm	1090*1010*2000mm	1280*1030*1980mm	
Package Size (W*D*H)	1120*1080*2010mm	1280*1080*2150mm	1280*1080*2150mm	1410*1080*2130mm	
Net Weight	245kg	285kg	300kg	320kg	
Gross Weight	288kg	345kg	370kg	405kg	

-60°C Freezer



Technical Parameters

Model	BDF-60H58		BDF-60H118A	BDF-60H218	BDF-60H318	BDF-60H458
Capacity	58L		120L	220L	320L	458L
Temp. Range	-10--60°C					
Temp. Accuracy	0.1°C					
Temp. Uniformity	±2°C				±4°C	
Temp. Stability	±2°C				±4°C	
Control System	Microprocessor control					
Display	LED display					
Alarm	High and low temperature alarm, thermostat fault alarm					
Refrigeration Type	Direct-cooling					
Refrigerant	R404A/R23 160g	R404A/R23 220g	R404A/R23 260g	R404A/R23 410g	R404A/R23 380g	
Compressor	International famous brand compressor /1					
Condenser & Evaporator	Copper tube aluminum fin condenser; cabinet-wrapped copper tube evaporator					
Defrost	Manual defrost					
Construction	Polyurethane cyclopentane foam					
Material	Internal Material	304 stainless steel				
	External Material	Sprayed steel plate				
Door	Outer door: sprayed steel plate outer door*1 Interior door: /					
Consumption	350W	340W	400W	480W	520W	
Power Supply	AC 220V, 50Hz(Standard); 110/220V, 60Hz(Optional)					
Casters	Yes					
Shelf	/					
Standard Accessory	Test hole					
Optional Accessory	Temperature recorder					
Internal Size (W*D*H)	410*410*385mm	696*470*385mm	960*470*595mm	1330*470*595mm	1380*500*690mm	
External Size (W*D*H)	670*765*1025mm	900*765*945mm	1160*765*885mm	1530*765*885mm	2115*895*1095mm	
Package Size (W*D*H)	740*835*1195mm	1020*830*1075mm	1230*835*1055mm	1600*835*1055mm	2185*965*1260mm	
Net Weight	83kg	88kg	106kg	126kg	207kg	
Gross Weight	110kg	128kg	143kg	170kg	255kg	