

Laboratory Water Purifier



Features:

- * Nano RO membrane filters tiny substances more efficiently.
- * Fully automatic control, one-key boot, simple operation.
- * With high pressure and low pressure protection, safer operation.
- * With consumable replacement alarm.
- * Compliance with national standard GB/T6682-2008 water requirements.

Technical Parameters:

Model		SCSJ-I-10L	SCSJ-I-15L
Water Output Type		RO water outlet*1 and DI water outlet*1	
Water Output Speed		10 L/H	15 L/H
Purifying Procedure		PF+AC+RO+DI	
Water Supply Requirement		When working, the inlet water pressure is 0.1~0.3Mpa, and the water quality meets the requirements of GB5749, 5~45°C	
Environmental Requirements		Temperature 15~35°C Relative Humidity ≤80%	
Purification System		10"PP filter*1, 10"active carbon filter*2 50GPD RO membrane *1 Deionization purification column*2	
DI Water Quality	Resistivity	10~18.25MΩ.cm	
	Conductivity	0.055~0.1μs/cm	
	Heavy metal	<0.1ppb	
	Particle	<1/ml	
	Bacteria	<0.1cfu/ml	
RO Water Quality	Ion rejection rate	96%~99%	
	Organic rejection rate	>99%	
	Particles and bacteria rejection rate	>99%	
Flow Rate		167ml/min	250ml/min
Consumption		46W	
Power Supply		AC220V, 50/110V, 60Hz (Standard). AC220V, 60Hz;110V, 50Hz (Optional)	
Standard Configuration		Main body	
Instrument Size(W*D*H)		390*400*503mm	
Package Size(W*D*H)		500*520*650mm	
Gross Weight		27kg	

Water Purifier (Automatic RO/DI Water)



Technical Parameters:

Model		SCSJ-III 15	SCSJ-III 30
Display		LCD	
Water Output Type		RO and DI water	
Water Output Speed		15L/H	30L/H
Purifying Procedure		PF+AC+RO+DI	
Water Supply Requirement		Tap water: TDS<200ppm, 5~45°C, 1.0~4.0Kgf/cm² (If inlet TDS>200ppm, extra pretreatment filter is recommended)	
Purification System	Pretreatment unit	Folded composite filter element*1 Active carbon filter *1	Folded composite filter element*1 Active carbon filter *1
	RO unit	100GPD RO membrane*1	200GPD RO membrane*1
	Subsequent unit	Deionization purification column (imported resin) *2	Deionization purification column (imported resin) *3
Pure Water Quality	Ion rejection rate	97%~99% (New RO membrane)	
	Organic rejection rate	>99%, when MW>200 Dalton	
	Particles and bacteria rejection rate	>99%	
	Resistivity	15~18.2MΩ·cm	
		Conductivity	
		0.055~0.067μs/cm	
Control System		Automatic electronic pressure sensor controlling, RO membrane auto flushing, Automatic stop when water supply shortage, Automatic stop when water tank full, Automatic cutting off water when pump stop, 24 hours non-stop work	
Flow Rate		2.0 L/min (when there is water in the water tank)	
Water Quality Monitor		TDS/conductivity test pen	
Consumption		72W	
Power Supply		AC220V, 50/60Hz; AC110V, 50/60Hz	
Standard Configuration		Main body(include1 set of purification column),15Lwater tank, TDS/conductivity test pen,accessory pack	
External Size(W*D*H)		410*220*420mm	
Package Size(W*D*H)		600*490*580mm	
Gross Weight		35kg	