BIOBASE®

Washer Disinfector (Lab Automatic Glassware Washer)



The lab glassware washers integrate programmed cleaning, disinfecting and drying functions to clean all glassware stuff, for beaker, flask, pipette, petri dish, burette, measuring cylinder, test tube etc.

Features:

- * High efficient cleaning system, designed with European reliable pump, optimized spray arm and nozzles, and self-cleaning program;
- * Rapid and efficient drying system, designed with independent air heater, HEPA filter and drying process;
- * Water heating temperature can reach 99°C, while hot air drying temperature can reach 120°C;
- * Professional configuration design—stainless steel for corrosion resistance; reinforced glass window mounted to achieve a clear view on washing process;
- * PLC touch screen control with preset 12 programs and 99 cutomized programs
- * Safety protection—electronic security door lock to prevent unexpected door opening, water & drying air temperature dual control and equipped with emergency switch.

Standard Washing Procedure (can be self-designed by the user):

 $Pre-cleaning \rightarrow Washing \ with \ cleaner \rightarrow Rinse \rightarrow Washing \ with \ neutralization \rightarrow Rinse \rightarrow Washing \ with \ hot \ water \rightarrow Drying$

All cleaning racks can be removed completely, convenient to washing rack pipeline:



Standard Rack (BKIR36)



Beaker Rack (BKBR01)



Combined Rack (BKIR11218)



Measuring Cylinder Rack (BKIR38)



Injection Rack (BKIR30)

Petri-dish Rack-Lower (BKPDR9070L)



Petri-dish Rack-Upper (BKPDR9070U)



Pipette Rack (BKPR60)



Rubber Tube Rack (BKRTR20)

Technical Parameters:

Model	BK-LW120	BK-LW220	BK-LW320
Capacity	120L	220L	320L
Water Consumption/Cycle	17L X 9 0 1 1 (0)	20L 0656	22L
Inlet Water Pressure	0.3~0.8Mpa		
Noise	≤50dB	≤55dB	e.com
Material	Internal materia: SS316, Outer material: SS304		
Overall Power Consumption	6KW	6/17KW	
Power Consumption-Water Washing	0.75KW	1.5 KW	
Power Consumption-Water Heating	5KW	5/15KW	
Power Consumption-Drying	3KW	3.6KW	
Power Supply	AC220V, 50Hz(Standard); 110V,60Hz(Optional)	AC220V, 50Hz; 380V, 50Hz(Standard); 110V,60Hz(Optional)	
Cleaning Racks	1 pcs	2 pcs	3 pcs
Standard Cleaning Racks	BKIR36*1	BKIR36*2	BKIR36*3
Standard Accessories	USB interface		
Optional Accessories	Cleaning racks		
Washer Chamber Size(W*D*H)mm	600*629*465	600*629*690	600*629*820
External Size(W*D*H)mm	980*740*870	690*790*1820	690*790*1970
Package Size(W*D*H)mm	1060*940*1030	790*940*1990	790*940*2100
Gross Weight(kg)	203	300	320

47 48