




Doppler Fetal Monitor




Features:




Precise measure




Clear fetal sound




High sensitivity




Rechargeable batteries




Intelligent noise reduction



Zero microradiation




Notice light




Compact and portable

Applications:
Doppler Fetal Monitor is a small and portable fetal heart rate monitoring instrument. It is suitable for fetal heart rate detection and fetal heart sound monitoring for middle and late pregnancy women. Using intelligent noise reduction technology, the fetal sound is clear, the measurement is accurate, safe and reliable, and it is a common fetal monitoring instrument for obstetrics and families.



Technical Parameters:	
Model	BK-TH-8A
External Size	75*180*30mm
Net Weight	260±20g(include battery)
Ultrasonic Output Intensity	100mW/cm2
Ultrasonic Output Power	8mW
Nominal Acoustic Operating Frequency	3.0MHz
Measuring Precision	1bpm
Measuring Accuracy	±2bpm
ATM Range	70kPa-106kPa
Ambient Temp. Range	5-40℃
RH Range	30%-80%
Battery Information	DC9.6V battery
Power Supply	100V-240V, 50/60Hz
Packing Size	310*225*90mm
Gross Weight	1.1kg

Pulmonary Function Tester



Introduction:
Pulmonary function tester is a medical device used to measure the volume of air inhaled and exhaled by the lungs. It can perform lung function tests and track the health of the lungs. vital capacity, maximal minute ventilation and resting minute ventilation), physical examination tests, diastolic tests.

Features:
Meets American Thoracic Society standards
Well-known brand high-precision flow sensor
Can store about 1000 results
8 inch full touch screen display
Built-in high-performance thermal printer.

Technical Parameters:	
Model	BK-LFT-1
Display	8 inch touch screen
Resolution	1024*768
Color Depth	65K
Printer	Built-in
Printing Paper	Thermal paper 80mm*30mm
Printing Speed	50mm/s
ambient temperature	5-40℃
Relative humidity	≤80%RH
ambient Pressure	70~106 kPa
Volume range	0~10L
Volume accuracy	±3% or ±0.05 L (whichever is greater)
Flow Range	0~14L/s
Flow accuracy	±5% or ±0.17 L/s (whichever is greater)
External Size(L*W*H)	240*210*165(mm)
Power supply	AC220V, 50/60Hz(Standard); 110V, 60Hz(Optional)
Package Size(L*W*H)	570*415*240mm
Gross Weight	5.5kg

471

472