

Biosafety Accessories

Electric Height Adjustable Base Stand



APPLICATIONS

For biosafety cabinet, laminar flow cabinet, fume hood and other laboratory equipment which need adjustable height base stand.

FEATURES

1. Heavy load and smart balance
2. Smooth running speed and low noise
3. Concise and easy with nice appearance
4. Low maintenance cost
5. Easy to install and disassemble
6. Max Adjustable Route 400 mm
7. Width adjustable is customized
8. Multipurpose for laboratory apparatus



Control Button



Footmaster Caster

TECHNICAL PARAMETERS

| Max Route(mm) | 100 | 150 | 200 | 250 | 300 | 350 | 400 |
|------------------------------|---|-----|-----|-----|-----|------|------|
| Height of Min.Height(mm) | 440 | 490 | 540 | 590 | 640 | 690 | 740 |
| Base Stand Max.Height(mm) | 540 | 640 | 740 | 840 | 940 | 1040 | 1140 |
| Max Load | 400kg | | | | | | |
| Load Speed | 5mm/s | | | | | | |
| Working Frequency | 10%, max continuous working time is 2 minutes | | | | | | |
| Noise | <65dB | | | | | | |
| Work Temperature | -26°C~65°C | | | | | | |
| Pedestal: 3.0mm steel | | | | | | | |
| Lifting Rod: Aluminium alloy | | | | | | | |
| Power Supply | AC220V±10%, 50/60Hz; 110V±10%, 60Hz | | | | | | |
| Controller Consumption | 100~200W | | | | | | |
| Caster | Footmaster Caster | | | | | | |
| Applications | For biosafety cabinet, laminar flow cabinet, fume hood and other laboratory equipment | | | | | | |



Air Velocity Meter

Measurement Range: 0~30m/s
Accuracy: $\pm 3\%$ or ± 0.015 m/s
Resolution: 0.01m/s
Data log 12,700+samples and 100 test IDs
The 9535 model comes with a telescopic straight probe.
The 9535-A model comes with an articulated probe.



Dust Particle Counter

Particle Size Channel: 0.3, 0.5, 1.0, 3.0, 5.0, 10.0(μ m)
Sampling period: 1~9999s
Number of sampling point: 2~9
Sampling frequency: 2~9
Sampling quantity: 2.83L/min(0.1cfm)



Digital Sound Level Meter

Measurement Range: 30~130dB
Accuracy: ± 1.5 dB
Resolution: 0.1dB



Illumination Meter

Light Intensity range: 0~200,000LUX
Accuracy: $\pm 3\%$ rdg $\pm 0.5\%$ f.s. (<10,000lux)
 $\pm 4\%$ rdg ± 10 dgts (>10,000lux)



BK-HM35 BK-HM15

Infrared Sterilizer

Two types:
BK-HM35: 35mm dimension of cavity
BK-HM15: 15mm dimension of cavity
Setting Temperature: 3-level: 400°C, 620°C, 840°C
Heating Time: Less than 15 minutes
Power: 240W
Power Supply: Standard: AC220V, 50/60Hz;
Optional: AC110V, 50/60H
Packing Size: 300*250*200mm
Gross Weigh: BK-HM35: 1.5kg; BK-HM15: 1.3kg



Foot rest

Humanization design.
Material is cold-rolled steel with anti-bacteria powder coating.
Can be customized.



Formalin Fumigation Sterilizer Ammonium Hydrogen Carbonate Neutralizer

Sterilize the cabinet with formalin for 8 hours and neutralize the formalin with ammonium hydrogen carbonate for 8 hours.



Arm rest

Alleviate fatigue on operator's armsPrevent air obstruction
Adjustable height range: 85~100mm



Laboratory Chair

Backrest and seat material: Artificial leather
Seat diameter: 350mm
Backrest height: 420mm
Height range: 500~700mm