Table Top Full-automatic Glassware Washer

Introduction:

The small and flexible Mini body can be placed on the table to maximize the immediacy of cleaning and convenience.

It is suitable for cleaning utensils with small cleaning amount and laboratories with many cleaning tasks, eliminating manual cleaning consumes time and effort, meanwhile greatly reducing operating costs.

Features:

∗ Wide cleaning range, covers 1.5ml~100ml of all kinds of sample bottles, test tubes, centrifugal tubes, beakers, volumetric flask, triangle flask and other common laboratory utensils.

∗ The cleaning rack can be flexibly selected according to the cleaning items, and is highly compatible with common laboratory utensils.

∗ Microcomputer control system, stable performance, reliable quality.

∗ Complete functions, including standard washing, strengthening washing, fast washing three modules, covering most of the cleaning scenarios.

∗ Real-time display of operating data, water temperature, time, cleaning agent dosage can be freely set.

∗ Small size, less water, electricity, cleaning agent consumption, energy saving and environmental protection.

Cleaning Racks:

BKIR36B Standard Rack

BKIR52B Injection Rack

BKIR126B Tube/Celine bottle cleaning rack

BKIR6018B Combined Rack

BKBR02B Medical apparatus cleaning rack

BKBR04B Test tube cleaning rack

BKPDR9024B Petri-dish cleaning rack

Technical Parameters:

Model		BK-LW60
Cleaning	Capacity(L)	90
	Washer Load Level	1
	Water Wash Power(kW)	0.25
	Water Heater Power(kW)	3
	MAX. Power(kw)	3.5
	Water Consumption/Step(L)	8
	Tank Internal Temperature(℃)	0~99
	Water Supply Pressure(Mpa)	0.3~1.0
	Peristaltic Pump for Cleaning Agent	2 independent pumps control detergent agent and neutralizing agent
	Cleaning Agent Level Sensor	YES
	Washing Pump	Sweden 150L/min
	Standard Cleaning Racks	Select the following cleaning rack (one)
Drying	Drying Function	NO
	Steam Condenser	NO
	Dry Power (kW)	NO
Control System and Traceability	Control System	4.3" color LCD touch screen display, microprocessor
	Cleaning Program	3 pre-set programs(editable)
	Password Protection	3 levels password
	Safety Emergency Button	NO
	USB port	YES
	Integrated printer	NO
	Online Monitor Performance of Washing	NO
Dimensions& Weight	Chamber Dimension(W*D*H,mm)	470*462*422
	Exterior Dimension(W*D*H,mm)	529*648*650
	Package Dimension(W*D*H,mm)	650*780*850
	Net Weight(Host only, kg)	65
	Gross Weight(Host with rack, kg)	104
Others	Door	Foam SS door
	Safety Door Lock	YES
	Built-in RO Water Pump	YES
	Noise(dB)	<50
	Voltage(V/Hz)	Standard: AC220V, 50Hz; Optional: AC220V, 60Hz; 110V, 60Hz