

Combination Emergency Shower Eye Washer



- Features:**
- * Material: stainless steel 304, fine polish/high brightness antioxidant coating.
 - * Assembling feature: the "Union" allows easier pipe connection and disconnection.
 - * Usage: drenching body and rinsing faces / eyes can be operated separately or simultaneously.
 - * Shower & eye wash switch: two-piece ball valve.
 - * Shower head: spinning-formed with curled rim, diameter 250 mm.
 - * Pipe diameter: 38 mm.
 - * Nominal pressure: 1.0 Mpa.
 - * Working pressure: 0.2~0.4 Mpa.
 - * Testing pressure: 1.5 Mpa.
 - * Temperature requirement on working environment: 0~40°C.
 - * Flow rate of body shower: ≥76 L/min.
 - * Flow rate of eye/face wash: ≥11.4 L/min.
 - * Eyewash bowl features: 300 mm in diameter, vertical bowl-wall design, allows better water collecting and anti-splashing.
 - * Dust cover: integrated with the spray head(Not connected by chain), and easily removed by water flow.
 - * Spray head feature: patented design, each spray head equips with one water-flow control valve.
 - * Inlet thread: Rp 1", female
 - * Outlet thread: Rp 1", female
 - * Inlet height(From above the floor): 1160 mm
 - * Outlet height(From above the floor): SEW-C1: 86 mm, SEW-C2: 90 mm.
 - * Distance between spray heads: 170 mm
 - * Water pattern coverage: at the height of 1520 mm above floor, the water pattern covers a circular area of at least 510 mm in diameter.
 - * Notes: the inlet part and outlet part are customizable; shutoff valve and filter are proposed to be equipped on the water-supply end.
- Stainless steel-made foot treadle is optional as eye wash switch(For SEW-C1).

Technical Parameters:

Model	SEW-C1	SEW-C2
Package Size(W*D*H)	1310*380*300mm	1245*355*460mm
Gross Weight	17.5kg	20kg

Fiber Analyzer



- Features:**
- * 16-bit true-color 7-inch touchscreen; intuitive UI enabling one-hand operation.
 - * On-board storage for 50 user-defined protocols.
 - * 5 independent user accounts, supporting password or fingerprint login.
 - * Role-based access control, each account can be assigned a customized function set.
 - * Built-in self-diagnostics for all moving parts; on-screen status display for quick maintenance.
 - * Special-alloy reactor: resistant to high temperature, high pressure and corrosion; service life over 10,000 cycles.
 - * Dual dry-run protection (hardware + software).
 - * Automatic air-tightness check before and during operation; alarm for lid leakage.
 - * Anti-foam chamber design, no defoamer required, odor-free.
 - * High-power aluminum heating block for rapid, uniform heating.
 - * Closed digestion: steam containment, enabling micro-boiling without cooling water.
 - * ±0.2 °C PID control via in-vessel PT1000 sensor.
 - * Real-time pressure monitoring; automatic pause and pop-up alarm when limits are exceeded.
 - * Audible and visual prompts upon test completion.
 - * Three built-in fiber calculation formulas; automatic result printing after sample mass input.

Technical Parameters:

Model	BK-F1600		
Processing Temperature Range	Room temperature ~100℃	Sample Batch Capacity	1~24
Sampling Amount/Bag	0.5~1.5g	Adding Method	Manual
Fiber Test Range	0.1~100%	Temperature Control Accuracy	±0.2℃
The Cooking Time Setting of Each Stage	0~999min		
Repeatability Accuracy	If the fiber content is less than 10%, the relative deviation is ≤5%; If the fiber content is greater than 10%, the relative deviation is ≤3%		
Daily Processing Capacity	24~96 pieces of crude fiber, 24~120 pieces of neutral detergent fiber/acid detergent fiber/lignin(8-hour working system)		
External Size(W*D*H)	560*430*510mm		
Net Weight	28kg		
Package Size(W*D*H)	660*500*590mm		
Gross Weight	44kg		