

## Vertical Type Shaking Incubator



BJPX-SL10/BJPX-SL20

BJPX-SL10-L/BJPX-SL20-L

### Features:

- \* Large hollow electric heating perspective window, anti-condensation, convenient for customers to check the running condition of the box.
- \* The display interface has the functions of historical data, curve, alarm record can be queried, data can be saved and exported, password lock screen protection and Chinese and English switching.
- \* Humanized design of the door stop function, to protect the safety of personnel.
- \* Box padding foot height adjustable, standard universal casters, easy to move the box.
- \* Professionally designed side air vents to meet the oxygen requirement of samples.

### Technical Parameters:

Model	BJPX-SL10-L		BJPX-SL10		BJPX-SL20-L		BJPX-SL20	
Display	LCD		7 inch touch screen		LCD		7 inch touch screen	
Circulation Mode	Forced convection							
Shaking Mode	Rotary shaking							
Drive Mode	Three axis balanced drive type							
Vibration Range	Φ26mm							
Rotating Speed	30~300rpm							
Rotating Accuracy	±1r/min							
Temp. Range	RT+5~60℃				4~60℃			
Temp. Control Accuracy	0.1℃							
Temp. Uniformity	≤±1℃(37℃)							
Temp. Fluctuation	≤±0.5℃							
Timing Range	0~9999min(h)		0~999h59min		0~9999min(h)		0~999h59min	
Shaking Plate Size	413*466mm (Two layers)							
Max. Capacity	Upper layer: 100ml*25 or 250ml*16 or 500ml*12 or 1000ml*9 (Flask clamp)							
	Lower layer: 100ml*20 or 250ml*12 or 500ml*9 or 1000ml*6 (Flask clamp)							
	tube rack*2 96-well plate*16 clamping rod shaking plate*2							
Standard. Capacity	Upper layer: 250ml*12 or 500ml*9 or 1000ml*6 (Flask clamp) Lower layer: Universal spring rack							
Lighting Mode	LED lamp*1							
Sterilization Mode	UV lamp*1							
Refrigerant	/				R134A			
Ambient Temp.	15~35℃							
Curve Programming	Fixed value		Fixed and multi-stage		Fixed value		Fixed and multi-stage	
Internal Material	304 stainless steel							
Consumption	850W				1000W			
Power Supply	AC 220V, 50/60Hz(Standard); 110V, 50/60Hz(Optional)							
Internal Size(W*D*H)	495*505*630mm							
External Size(W*D*H)	650*785*1135mm							
Package Size(W*D*H)	780*920*1290mm							
Net Weight	120kg				145kg			
Gross Weight	140kg				165kg			

### Note:

1. The height of the container placed in the clamping rod shaking plate is no more than 215mm.
2. The total height of the tube placed in the tube rack is less than 160mm (if the tube has a stopper, the total height of the tube should be counted as the height of the stopper).