

Differential Thermal Analyzer



Application:
Differential thermal analysis (DTA) is a technique that measures the temperature difference between a substance and a reference material under programmed temperature control. A DTA curve describes the relationship between the temperature (ΔT) of the sample and reference material as a function of temperature or time.
In a DTA experiment, changes in sample temperature are caused by endothermic or exothermic effects of phase transitions or reactions. Examples include phase transitions, melting, crystal structure changes, boiling, sublimation, evaporation, dehydrogenation, fracture or decomposition reactions, oxidation or reduction reactions, lattice structure disruption, and other chemical reactions.

Features:

- * USB bidirectional communication makes operation more convenient.
- * A 7-inch full-color LCD touch screen provides a user-friendly interface.
- * A nickel-chromium alloy sensor is highly resistant to high temperatures, corrosion, and oxidation.
- * A wide temperature range meets the testing needs of various materials.
- * Supporting analysis software enables real-time acquisition of measurement patterns and online analysis.

Technical Parameters:	
Model	BK-DTA3320A
Temperature Range	RT~1200°C
Temperature Resolution	0.01°C
Temperature Accuracy	±0.1°C
Temperature Repeatability	±1.5°C
Measuring Range	0 to ±2000μV
DTA Accuracy	0.01μV
Heating Rate	0.1~100°C/min
Atmosphere Control	Automatic switching of internal programs
Data Interface	Standard USB interface with included data cable and operating software
Power Supply	Standard: AC220V 50/60Hz, optional: AC110V 50/60Hz
External Size(L*W*H)	512*460*400mm
Net Weight	21.2kg
Packing Size(L*W*H)	660*590*500mm
Gross Weight	37.5kg

Differential Scanning Calorimeter



Application:
Differential scanning calorimeter can be used to test glass transition temperature, phase transition, melting and thermal enthalpy, product stability, oxidation induction period, specific heat, etc. It is mainly used in the chemical, energy, metallurgy, mining, polymer materials, metal materials and other industries.

Features:

- * Industrial-grade 7-inch touch screen displays rich information.
- * Brand-new metal furnace structure provides a better baseline and higher accuracy.
- * USB communication interface for versatility, reliable and uninterrupted communication, and supports self-recovery.
- * Automatically switches between two atmosphere flow rates with fast switching and short stabilization time. Also includes an additional shielding gas input.
- * Simple and easy-to-use software.

Technical Parameters:			
Model	BK-DSC300	BK-DSC300C	BK-DSC300L
Temperature Range	RT~600°C	-35~600°C	-150~600°C
Temperature Resolution	0.001°C		
Temperature Fluctuation	±0.001°C		
Temperature Repeatability	±1°C		
Heating Speed	0.1~80°C/min	0.1~100°C/min	0.1~100°C/min
Cooling Speed	/	0.1~20°C/min	0.1~40°C/min
Constant Temperature Time	Program setting ≤24h	Program setting ≤24h	0~400min
Temperature Control Method	Heating, constant temperature, cooling		
DSC Range	0 to ±600mW	0 to ±600mW	0 to ±600mW
DSC Resolution	0.01μW		
DSC Sensitivity	0.001mW		
Gas Flow	0~200mL/min	0~200mL/min	0~300mL/min
Gas Pressure	≤0.5MPa	≤0.5MPa	≤0.2MPa
Power Supply	Standard: AC220V 50/60Hz, optional: AC110V 50/60Hz		
External Size(L*W*H)	488*428*237mm		
Net Weight	13.4kg	15kg	15.3kg
Packing Size(L*W*H)	615*545*490mm	Main Unit: 615*545*490mm; Accessory: 540*455*815mm	Main Unit: 615*545*490mm; Accessory: 600*600*1180mm
Gross Weight	26.2kg	Main Unit: 28.5kg; Accessory: 41.6kg	Main Unit: 29.6kg; Accessory: 70kg