


5-Part Auto Hematology Analyzer BK-6310



Features:

- ①. Throughput: 60T/H.
- ②. 14-inch touch screen.
- ③. Tri-angle laser scatter + flow cytometry method + impedance method for counting.
- ④. 3D holographic scattergram displays the accurate 5-part differentiation of WBC.
- ⑤. Large storage capacity: 100,000 results (including histogram, scattergram, patient information).

Parameters:

| Model | BK-6310 | | | |
|----------------------|---|--|-----------------|--|
| Throughput | 60 Tests/hour | | | |
| Assay Items | 5 parts, 29 parameters, 3 histograms, 3D scattergram | | | |
| Principle | Tri-angle laser scatter, Flow cytometry method, 3D scattergram analysis, Impedance method for RBC and PLT counting, Cyanide free reagent for HGB test | | | |
| Test Mode | CBC mode, CBC+DIFF mode Venous whole blood, Capillary whole blood and Prediluted | | | |
| Parameters | WBC, RBC, HGB, HCT, MCV, MCH, MCHC, RDW-SD, RDW-CV, PLT, MPV, PCT, PDW, P-LCR, P-LCC, NEU%, LYM%, MON%, EOS%, BAS%, NEU#, LYM#, MON#, EOS#, BAS# 4 research parameters: ALY%, ALY#, IG%, IC# | | | |
| Performance | Item | Linearity range | Carry Over | |
| | WBC | 0~300*10 ⁹ /L | ≤ 0.5% | |
| | RBC | 0~8.00*10 ¹² /L | ≤ 0.5% | |
| | HGB | 0~250g/L | ≤ 0.5% | |
| Performance | PLT | 0~3000*10 ⁹ /L | ≤ 1.0% | |
| | Sample Volume | CBC+DIFF mode: ≤20μl | CBC mode: ≤10μl | |
| | Storage | 100,000 results including histogram, scattergram and patient information | | |
| | Interface | 4 USB ports, 1 LAN port Bi-direction LIS, support HL7 protocol, Internal RFID reader | | |
| Power Supply | AC220V±10% 50/60Hz; 110V±10% 60Hz; 400VA | | | |
| Package Size(W*D*H) | 575*490*690mm | | | |
| Gross Weight | 46kg | | | |
| Reagent Package Size | 330*330*330mm, 400*290*240mm, 400*290*240mm | | | |
| Reagent Gross Weight | 22kg, 2kg, 2kg | | | |

5-Part Auto Veterinary Hematology Analyzer BK-6310VET



Features:

- ①. Throughput 60T/H.
- ②. 14-inch touch screen.
- ③. Tri-angle laser scatter + flow cytometry method + impedance method for RBC and PLT counting.
- ④. 3D holographic scattergram displays the accurate 5-part differentiation of WBC.
- ⑤. Large storage capacity: 100,000 results (including histogram, scattergram, animal information).

Parameters:

| Model | BK-6310VET | | | |
|----------------------|--|---|-----------------|--|
| Throughput | 60 Tests/hour | | | |
| Sample Profile | Dog, cat, horse, sheep, goat, camel, cow, more species coming soon | | | |
| Assay Items | 5 parts, 25 parameters, 3 histograms, 3D scattergram | | | |
| Principle | Tri-angle laser scatter, Flow cytometry method, 3D scattergram analysis, Impedance method for RBC and PLT counting, Cyanide-free method for HGB test | | | |
| Test Mode | CBC mode, CBC+DIFF mode Venous whole blood, Capillary whole blood and Prediluted | | | |
| Parameters | WBC, RBC, HGB, HCT, MCV, MCH, MCHC, RDW-SD, RDW-CV, PLT, MPV, PCT, PDW, P-LCR, P-LCC, NEU%, LYM%, MON%, EOS%, BAS%, NEU#, LYM#, MON#, EOS#, BAS# | | | |
| Performance | Item | Linearity range | Carry Over | |
| | WBC | (0~300.0*10 ⁹)/L | ≤0.5% | |
| | RBC | (0~8.00*10 ¹²)/L | ≤0.5% | |
| | HGB | (0~250)g/L | ≤0.5% | |
| Performance | PLT | (0~3000*10 ⁹)/L | ≤1.0% | |
| | Sample Volume | CBC+DIFF mode: ≤20μl | CBC mode: ≤10μl | |
| | Storage | 100,000 results including histograms, scattergrams and patient information | | |
| | Interface | 4 USB ports, 1 LAN port, Bi-direction LIS, support HL7 protocol, Internal RFID reader | | |
| Power Supply | AC100~240V±10% 50/60Hz; 300VA | | | |
| Package Size(W*D*H) | 575*490*690mm | | | |
| Gross Weight | 46kg | | | |
| Reagent Package Size | 330*330*330mm, 400*290*240mm, 400*290*240mm | | | |
| Reagent Gross Weight | 22kg, 2kg, 2kg | | | |