




ETL Certified Horizontal Laminar Flow Cabinet



**Stainless Steel I.V.
Bar with 10 hooks**



Waterproof Socket
America Standard



Footmaster Caster
Universal caster with brake
and leveling feet



Wind Speed Sensor
Direct measurement of wind speed

ADVANTAGE

1. ETL certification, Satisfy North American market.
2. With memory function in case of power-failure.
3. Audio and visual alarm (Abnormal airflow velocity).

TECHNICAL PARAMETERS

Model	BBS-H800	BBS-H1100	BBS-H1300	BBS-H1500	BBS-H1800
External Size(W*D*H)	800*810* (1720~1980)mm	1100*810* (1720~1980)mm	1300*810* (1720~1980)mm	1500*810* (1720~1980)mm	1800*810* (1720~1980)mm
Internal Size(W*D*H)	700*500*600mm	1000*500*600mm	1200*500*600mm	1400*500*600mm	1700*500*600mm
Work Surface Height	750~1010mm				
Max Opening	440mm				
Display	LCD Display				
Airflow Velocity	80~99fpm				
Material	Working area: 304 stainless Steel. Main Body: Cold-rolled steel with anti-bacteria powder coating. Front Window: 5 mm toughened glass, anti-UV.				
Pre-Filter	Polyester fiber				
HEPA Filter	One, 99.995% efficiency at 0.3μm				
Noise	≤68dB(A)				
Illumination	≥300lx				
Waterproof Sockets	One socket (Double type), America standard, Max.Power: 500W				
Power Supply	103.5~126.5V, 60Hz, 10A				
Consumption	750W	950W	950W	950W	1150W
LED Lamp	10W*1	14W*1	14W*1	18W*1	22W*1
Standard Accessory	Manually height adjustable base stand, LED lamp, wind speed sensor, waterproof socket, Stainless Steel I.V.Bar with 10 hooks				
Optional Accessory	UV lamp				
Package Size (W*D*H)	940*1090*1250mm	1240*1090*1250mm	1440*1090*1250mm	1640*1090*1250mm	1940*1090*1250mm
Gross Weight	150kg	190kg	225kg	265kg	300kg