



## Horizontal Laminar Flow Cabinet




**LCD Display**  
Airflow velocity, UV timer, UV work time, system work time, real time.



**Waterproof Socket**  
2 waterproof sockets are located in the side panel, for optimum convenience of using small devices inside the cabinet.



**Gas Tap**



**UV Lamp**  
Emission of 253.7 nanometers for most efficient decontamination



**Side Glass Window**  
The transparent side glass windows maximize light and visibility inside the cabinet, providing a bright and open working environment.

## TECHNICAL PARAMETERS

Model	BBS-H1300	BBS-H1800
External Size (W*D*H)	1300*820*2040mm	1800*820*2070mm
Internal Size (W*D*H)	1200*500*570mm	1700*500*570mm
Work Surface Height	750mm	
Display	LCD Display	
Airflow Velocity	Average of 0.3~0.5m/s	
Material	Main Body: Cold-rolled steel with anti-bacteria powder coating Work Table: 304 stainless steel Side and Front Window: 5mm toughened glass, anti-UV	
Pre-Filter	Polyester fiber, washable	
HEPA Filter	99.995% efficiency at 0.3µm	
Noise	<65dB	
Front Window	Motorized	
Max Opening	430mm	
LED Lamp	12W*1	16W*2
UV Lamp	30W*1	30W*1
	Emission of 253.7 nanometers	
Consumption	400W	500W
Waterproof Socket	Two, total loads500W	
Caster	Universal caster with leveling feet	
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz	
Standard Accessory	LED lamp, UV lamp*2, Base stand, Gas Tap, Waterproof socket*2 Water tap(only for BBS-H1800)	
Optional Accessory	Electric height adjustable base stand	
Gross Weight	254kg	328kg
Package Size(W*D*H)	1450*1060*1650mm	1950*1060*1600mm