

Double Door Automatic Glassware Washer



BK-LW220D/BK-LW320D

BK-LW420D



Standard cleaning rack(4 Layers)



Standard cleaning rack(5 Layers)



Toughened glass door (BK-LW220D/BK-LW320D)



LCD display

Features:

- * Two toughened glass doors, prevent cross infection.
- * Color LCD touch screen, advanced programmable control system with twelve standard programs.
- * High efficient cleaning system, with rotary nozzles in top, bottom and among the shelves to make sure that the spray liquid can contact the surface of devices completely.
- * High efficient drying system with HEPA filter, can clean and dry the inner of tubular things.
- * Thermal disinfection, water heating system can make sure the water temperature keep above 93°C to reach the international disinfecting efficiency level.

Standard Washing Procedure (can be self-designed by the user):

Pre-cleaning→Clean with enzymes →Rinse→Thermal disinfection→Glazing clean→Drying

Technical Parameters:

Model	BK-LW220D	BK-LW320D	BK-LW420D
Capacity	220L	320L	420L
Washer Load Level	2	3	2
Water Wash Power	0.75KW	1.5KW	1.5KW
Water Heater Power	5KW	5KW	5KW
MAX. Power	6KW	7KW	7KW
Water Consumption/Step	20L	22L	25L
Cleaning	Tank Internal Temperature 0~99°C Water Supply Pressure 0.3~1.0Mpa Peristaltic Pump for Cleaning Agent 2 independent pumps control detergent agent and neutralizing agent Cleaning Agent Level Sensor YES Washing Pump Sweden 800L/min Sweden 1000L/min Sweden 1000L/min		
	Standard Cleaning Racks 4 Layers	5 Layers	
	BK01-220*1	BK01-320*1	BK01-420*1
Drying	Drying Function YES Steam Condenser NO Dry Power 3.6KW 3.6KW 3KW		
Control System and Traceability	Control System 7" color LCD touch screen display, microprocessor Cleaning Program 12 pre-set programs(editable)+100 PLC free programming Password Protection 3 levels password Safety Emergency Button YES USB Port YES Integrated Printer YES Online Monitor Performance of Washing Optional		
Dimensions & Weight	Chamber Dimension(W*D*H) 600*629*830mm 600*629*990mm 688*700*703mm Exterior Dimension(W*D*H) 960*805*1865mm 960*805*2025mm 1110*900*2165mm Package Dimension(W*D*H) 1100*950* 2150mm 1100*950*2180mm 1230*1070*2290mm Net Weight(Host only) 320kg 340kg 370kg Gross Weight(Host with rack) 420kg 440kg 460kg		
Others	Door Double-layered glass door, 2 doors, manual Double-layered glass door, 2 doors, electric Safety Door Lock YES Built-in RO Water Pump YES Noise <55dB <55dB <60dB Optional Accessories Trolley(BK01) Power Supply AC220V, 50Hz; 380V, 50Hz(Standard); AC380V,60Hz; 220V, 60Hz ;220V, 60Hz(Three phase); 110V, 50/60Hz(Optional)		