

Electronic & Digital Heating Mantles



Features:

- * corrosion-resisting and ageing-resistant.
- * The internal heater is in hemisphere shape with high efficiency.
- * The external material is cold-rolled steel with anti-bacteria powder coating.
- * It adopts high-temperature resistant alkali-free glass fiber with good isolation performance.

Technical Parameters:

Model	HME-I (Electronic Display) / HMD-I(LED Display)											
Capacity(ml)	100	250	500	1000	2000	3000	5000	10000	20000	50000		
Max. Temp.	380℃											
Working Time	Continuous											
Consumption	100W	180W	250W	300W	500W	600W	1000W	1500W	2500W	6000W		
Power Supply	AC220/110V±10%, 50/60Hz											
Internal Size (mm)	Ф70*40	Ф95*50	Ф150*50	Ф150*70	Ф180*80	Ф200*100	Ф245*150	Ф310*175	Ф380*190	Ф480*270		
External Size (W*D*H)	200*215*150mm			240*260 *170mm	285*300 *200mm	355*300 *240mm	415*370 *270mm	480*430 *300mm	540*530 *280mm	665*450 *550mm		
Packing Size (W*D*H)	260*265*237mm			250*70 *190mm	300*310 *210mm	300*310 *245mm	370*380 *285mm	500*440 *320mm	560*560 *290mm	775*775 *560mm		
Net Weight	1.7kg	1.8kg	1.8kg	2.7kg	4kg	4.5kg	7kg	10kg	13kg	53kg		
Gross Weight	3.5kg	2kg	2kg	4kg	5.5kg	6kg	9kg	13kg	15kg	68kg		

Electronic & Digital Magnetic Stirring Heating Mantles



Features:

- * The internal heater is in hemisphere shape with high efficiency.
- * The external material is cold-rolled steel with anti-bacteria powder coating.
- st Stepless speed adjustment, uniform temperature, easy to operate with effective use.
- * It adopts high-temperature resistant alkali-free glass fiber with good isolation performance.
- * Stable precise stirring to liquid solution is within a wider speed scope, especially in the experiments of samples with small volume.

Technical Parameters:

Model	HME-II(Electronic Display) / HMD-II(LED Display)										
Capacity(ml)	100	250	500	1000	2000						
Max Use Temp.	380°C										
Speed	0~1200rpm										
Working Time	Continuous										
Max Use Temp.	380°C										
Consumption	consumption 100W		250W	300W	500W						
Power Supply	AC220/110V±10%, 50/60Hz										
Internal Size(mm)	Ф70*50	Ф90*60	Ф105*65	Ф135*80	Ф175*95						
External Size(W*D*H)	ternal Size(W*D*H) 220*195*165mm		220*195*165mm	280*260*205mm	320*300*215mm						
Packing Size(W*D*H)	acking Size(W*D*H) 295*290*255mm		295*290*255mm	350*345*305mm	385*380*340mm						
Net Weight	3kg	3kg	4kg	4kg	5kg						
Gross Weight 4kg		4kg	5kg	6kg	7kg						

57